

Concept 🚫 Pro

5MP 4mm Fixed Lens 30M



AIR3525DEEL-IP5M/4

Concept Pro 5MP IP Enhanced Low Light Fixed External Small Bullet Camera

The AIR3525DEEL-IP5M/4 model is an IP camera that has been designed to deliver the highest image quality for demanding external environments. This weather-resistant external small bullet features a 4mm fixed lens, smart infrared LEDs with 30m illumination range, and provides crisp 5-megapixel video. This camera is also designed for excellent compatibility with the Concept Pro range of network video recorders.



Deep Learning Motion Detection

Reduce false motion detection alarms by up to 95% using new Deep Learning Motion Detection technology. Trained with deep learning algorithms, the camera can recognise and trigger motion detection events only if a person is detected in the specified area. As a result, false alarms from sources such as lights, animals, foliage, weather, and other objects are effectively filtered and reduced.



Intelligent, Efficient Bit Rate Control

Reduce camera streaming bit rates by up to 90% by using Variable Bit Rate (VBR) or VBR+ smart bit rate control settings. These dynamic features maximise overall image quality while minimising camera stream bit rates. This results in lower network bandwidth usage and extended recording storage retention time.



Enhanced Low Light Performance

This model utilises an Enhanced Low Light CMOS sensor with greater light sensitivity, resulting in the camera capturing colour images long after standard CCTV cameras have switched to black & white night mode and brighter images in darker conditions.

KEY FEATURES

- Max. 25FPS @ 5MP
- 4mm Fixed Lens
- Up to 30m Smart IR Illumination
- Deep Learning Motion Detection
- H.265 Video Codec & VBR+
 Smart Bit Rate Control
- Enhanced Low Light Performance

OTHER FEATURES

- PoE/DC12V Power Input
- True WDR, ATW, BLC, Defog, 3D-DNR
- Manual Regions of Interest
- ONVIF Profile S Compliant
- IP66-rated



AIR3525DEEL-IP5M/4

Concept Pro 5MP IP Enhanced Low Light Fixed External Small Bullet Camera


SPECIFICATION


Model/Fea		AIR3525DEEL-IP5M/4
	Video Output Type	IP
	Image Sensor	1/2.8" Progressive Scan CMOS
	Signal System	PAL/NTSC
	Min. Illumination	Enhanced Low Light Performance -
		Colour: 0.004 Lux @ (F2.0, AGC ON) B&W: 0 lux with IR LEDs on
Camera	Electronic Shutter	Auto/Manual, 1/25 to 1/5,000s
	S/N Ratio	≥48dB
	IR LEDs	x4
	IR Illumination Range	Max. 30m
	IR Control	Auto/Off
	Adaptable IR	Auto
	Pan/Tilt/Rotation Range	P: 0°-360°, T: 0°-90°, R: 0°-360°
	Lens Type	Fixed Lens
	Mount Type	Built-in
	Focal Length	f=4mm
.ens	Aperture	F1.6
Video	Angle of View	H: 78.4° / V: 59.8° / D: 97.2°
	Focus	Fixed Focus
	Iris	Fixed Iris
	Compression	H.265/H.264 with VBR+ Smart Codec Option
	Streaming Capability	Triple Streaming + SVC Stream
	Resolution	2592x1944, 2592x1520, 2304x1296, 2048x1536, 1920x1080,
		1280x1024, 1024x768, 1280x720, 704x576, 704x480, 640x480,
		640x360, 352x288, 352x240
	Frame Rate	Stream 1: Max. 25FPS @ 2592x1944
		Stream 2: Max. 25FPS @ 640x480
		Stream 3: Max. 25FPS @ 640x480
	Bit Rate Control	CBR/VBR/VBR+
	Bit Rate	Stream 1: 1,000-8,000kbps
		Stream 2: 600-2,000kbps
		Stream 3: 600-2,000kbps
	Day/Night	True D&N with ICR (Auto/Day/Night/Schedule)
	Backlight Compensation	Yes
	Wide Dynamic Range	True WDR
	White Balance	ATW/Manual (Indoor/Fluorescent/Outdoor)
	Gain Control	Auto
	Noise Reduction	3D-DNR (Auto/Manual)
	Region of Interest	Manual (Max. 8 Regions)
	Defog	Yes
	Slow Shutter	Off/X2/X4/X8
	Image Setting	Mirror/Flip
	Image Adjustment	Brightness, Contrast, Colour, Sharpness
	Privacy Masking	Yes (Max. 4 Areas)
	Motion Detection	Yes (Max. 4 Areas)
	Tamper Detection	Yes
	Deep Learning Motion Detection	Yes (Human Detection)
	Deep Learning Video Analytics	-
	Transmission Distance	Max. 100m over Ethernet
Network	Ethernet	x1 RJ45 10M/100M Ethernet
	Protocol	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DN
		DDNS, NTP, SMTP, FTP, UPnP, HTTP, HTTPS, SSL/TLS
	Interoperability	ONVIF Profile S, HTTP/RTSP API
	ONVIF Channels	Max. 4 Streams
	Streaming Method	Unicast/Multicast
	Max. User Access	x10
	Edge Storage	Local PC (Snapshot/Recording)
	Video Interface	Ecolari o (onaparloti ilicording)
Interface	Alarm Interface	
	Audio Interface	-
	Audio Compression	N/A
	RS-485	-
	Control Protocol	N/A
	Reset Button	Yes
General	Power Supply	PoE 802.3af (Class 0)/DC12V
	Power Consumption	PoE: Max. 7.77W with IR on
	Power Output	-
	Operating Temperature	-20°C to +50°C
	Operating Humidity	0% to 90%
	Ingress Protection	IP66
		IPOO
	Vandal Resistance	- Alizzation Di II
	Housing Materials	Aluminum Diecasting
	RAL	RAL7021 Black Grey
	Dimensions	(Ø) 66mm × (L) 209mm without sunshield
	Net Weight	≈550g
	Gross Weight	≈700g


Concept 🚫 Pro

DIMENSIONS

All measurements are in mm.







ORDER CODE

AIR3525DEEL-IP5M/4

Concept Pro 5MP IP Enhanced Low Light Fixed External Small Bullet Camera

OTHER PRODUCTS IN THE RANGE

- AIR3525DEEL-IP5M-Z
 AIR3525DLEL-IP8M/2.8
 AIR3525DEEL-IP5M/2.8
- Concept Pro 5MP IP Enhanced Low Light Motorised External Small Bullet Camera Concept Pro 8MP IP Deep Learning Fixed External Small Bullet Camera Concept Pro 5MP IP Enhanced Low Light Fixed External Small Bullet Camera (2.8mm)

Concept Pro Small Junction Box - Black Grey

Concept Pro Small Wall Mount - Black Grey

Concept Pro Small Pendant Mount - Black Grey

Concept Pro Pole Mount

RECOMMENDED ACCESSORIES

- + CP-BASE-1-V2-G
- + CP-WM-1-V2-G
- + CP-PM-1-V2-G
- CP-PLM-V2
 - CP-CM-V2
 Concept Pro Corner Mount
 - CAT6-305 305m CAT6 Cable (Green)
 - VA-SW4/8/16POE-IP 4/8/16 Channel PoE Switch



AIR3525DEEL-IP5M/4

Concept Pro 5MP IP Enhanced Low Light Fixed External Small Bullet Camera



