



2MP

2.8mm Fixed Lens 30M IR

4 in 1 Analogue

AIR3525EL-AHD2M/2.8

Concept Pro Lite 2MP 4-in-1 Analogue Fixed External Small Bullet Camera

The AIR3525EL-AHD2M/2.8 model is a 4-in-1 analogue camera that has been designed to deliver the highest image quality for demanding external environments. This weather-resistant external small bullet features a 2.8mm fixed lens, smart infrared LEDs with 30m illumination range, and provides crisp 2-megapixel video at real-time frame rates with true wide dynamic range and enhanced low light performance. This camera is also designed for excellent compatibility with the Concept Pro range of hybrid digital video recorders.



True Wide Dynamic Range

With true wide dynamic range, this camera can capture sharp images throughout the entire field of view, even when there are severe differences between light levels.



Enhanced Low Light Performance

This CCTV camera utilises an Enhanced Low Light CMOS sensor with greater light sensitivity, resulting in the camera capturing colour images long after standard CCTV cameras have switched to black and white night mode.



Four-in-one solution

Don't be tied down to any single analogue platform. With Concept Pro 4-in-1 cameras you have the freedom to install whichever CCTV platform you like, whether you install AHD, TVI, CVI, or traditional analogue systems.

KEY FEATURES

- Max. 25FPS @ 2MP
- 2.8mm Fixed Lens
- Up to 30m Smart IR Illumination
- 4-in-1 Operation (AHD/TVI/CVI/CVBS)
- Enhanced Low Light Performance
- True Wide Dynamic Range

OTHER FEATURES

- DC12V Power Input
- Up the Coax Coaxitron Support
- AGC, Sens-up, AWB, BLC, HLC, Defog
- IP66-rated

ANALOGUE HD TYPICAL CABLE DISTANCE



DVR

	5MP	2MP	720P
COAX (RG59)	UP TO 500M	UP TO 500M	UP TO 500M
CAT5e	UP TO 200M	UP TO 305M	UP TO 350M
CAT6	UP TO 200M	UP TO 305M	UP TO 350M

 * Approximate distances calculated using HD MasterBaluns. Actual transmission range will vary depending on type and quality of cable and baluns.



AIR3525EL-AHD2M/2.8




Concept Pro Lite 2MP 4-in-1 Analogue Fixed External Small Bullet Camera


SPECIFICATION


Model/Featu	ure	AIR3525EL-AHD2M/2.8	
	Image Sensor	1/2.8" Progressive Scan CMOS	
	Video Output Type	AHD/TVI/CVI/CVBS	
	Signal System	PAL/NTSC	
	Min. Illumination	Colour: 0.02 lux (Enhanced Low Light) B&W: 0.002 lux (Enhanced Low Light) 0 lux with IR on	
Camera	Electronic Shutter	Auto/Manual, 1/25-1/25,600s	
	S/N Ratio	≥50dB	
	IR LEDs	x4	
	IR Illumination Range	Max. 30m	
	IR Control	On/Off	
	Adaptable IR	Auto	
	Pivot Axis	Pan: 0-360°, Tilt: 0-75°, Rotation: 0-360°	
	Lens Type	Fixed	
Lens	Mount Type	Built-in	
	Focal Length	f=2.8mm	
	Aperture	F2.0	
	Angle of View	H: 113.74°, V: 61.5°, D: 134.45°	
	Focus	Fixed	
	Iris	Fixed	
	Resolution	2MP (1920 x 1080), SD (960 x 576) AHD/TVI/CVI: 25/30FPS @ 2MP	
	Frame Rate	CVBS: 25/30FPS @ SD	
	Day/Night	True Day & Night with ICR (Auto/Colour/B&W/EXT)	
	Backlight Compensation	BLC/HLC	
	Wide Dynamic Range	True WDR	
Video	White Balance	Auto/AutoExt/Preset/Manual	
	Gain Control	Auto (AGC, 0-20)	
	Noise Reduction	2D/3D-DNR (High/Middle/Low/Off)	
	Motion Detection	Yes	
	Defog	-	
	Image Setting	Freeze, Flip	
	Image Adjustment	Brightness, Sharpness, Colour Gain, Ace, Gamma	
	Privacy Masking	Yes	
	Sens-Up	Yes (x2/x4/x8/x16/x32/Off)	
	Transmission Distance	Max. 500m (1Vp-p 75Ω)	
	Video Output	x1 1.0Vp-p 75Ω BNC (AHD/TVI/CVI/CVBS)	
	Audio Interface	-	
	RS-485	-	
nterface	Control Protocol	N/A	
	Up the Coax (Coaxitron) Support	Yes	
	OSD Buttons	Yes	
	Power Supply	DC12V±10%	
	Power Output	-	
	Power Consumption	- Max. 6W	
	Operating Temperature	-30°C to +50°C	
General	Operating Humidity	20–80% RH	
	Ingress Protection	IP66	
	Impact Resistance		
	Housing Materials	Aluminum Diecasting	
	RAL	RAL 7021 Black Grey	
	Dimension	(Ø) 66mm × (L) 209mm without sunshield	
	Net Weight	≈350g	
	Gross Weight	≈550g	
Certification	Certifications	CE	

DIMENSIONS

All measurements are in mm.







ORDER CODE

• AIR3525EL-AHD2M/2.8

Concept Pro Lite 2MP 4-in-1 Analogue Fixed External Small Bullet Camera

OTHER PRODUCTS IN THE RANGE

• AIR3525EL-AHD5M/2.8

Concept Pro 5MP 4-in-1 Analogue Fixed External Small Bullet Camera

RECOMMENDED ACCESSORIES

CP-BASE-1-V2-GCP-WM-1-V2-GCP-PM-1-V2-GCP-PLM-V2

Concept Pro Small Junction Box - Black Grey Concept Pro Small Wall Mount - Black Grey Concept Pro Small Pendant Mount - Black Grey Concept Pro Pole Mount Concept Pro Corner Mount

• CP-CM-V2 • RG59K-100 • RG59K-500

Concept Pro Corner Mount RG59 Coaxial Cable 100m (Black)) RG59 Coaxial Cable 500m (Black)

COMPATIBLE WITH

CONCEPT PRO AHD RECORDING RANGE

AIR3525EL-AHD2M/2.8



Concept Pro Lite 2MP 4-in-1 Analogue Fixed External Small Bullet Camera

ACCESSORIES

DIMENSIONS

CP-BASE-1-V2-G

Concept Pro Small Junction Box










CP-PM-1-V2-G

Concept Pro Small Pendant Mount





CP-WM-1-V2-G

Concept Pro Small Wall Mount













CP-PLM-V2

Concept Pro Pole Mount (can be combined with CP-BASE-1-V2)








CP-CM-V2

Concept Pro Corner Mount (can be combined with CP-BASE-1-V2)







COMPATIBLE WITH

