



5MP

2.7-13.5mm Motorised Lens 80M IR

4 in 1

# AIR8025EL-AHD5M-Z

## Concept Pro 5MP 4-in-1 Analogue Motorised External Bullet Camera

The AIR8025EL-AHD5M-Z model is a 4-in-1 analogue camera that has been designed to deliver the highest image quality for demanding external environments. This external bullet features a 2.7-13.5mm motorised lens, smart infrared LEDs with 80m illumination range, and provides crisp 5-megapixel video with true wide dynamic range and enhanced low light performance. This camera is also designed for excellent compatibility with the Concept Pro range of hybrid digital video recorders.



#### **True Wide Dynamic Range**

With true wide dynamic range, this camera can capture sharp images throughout the entire field of view, even when there are severe differences between light levels.



## **Enhanced Low Light Performance**

This CCTV camera utilises an Enhanced Low Light CMOS sensor with greater light sensitivity, resulting in the camera capturing colour images long after standard CCTV cameras have switched to black and white night mode.



## **DC12V Power Output**

This CCTV camera also provides a DC12V 100mA power output that can be conveniently used to power some auxiliary equipment rather than using a separate power supply adapter.

## **KEY FEATURES**

- Max. 20FPS @5MP
- ◆ 2.7-13.5mm Motorised Lens
- Up to 80m Smart IR Illumination
- ◆ 4-in-1 Operation (AHD/TVI/CVI/CVBS)
- Enhanced Low Light Performance
- True Wide Dynamic Range
- DC12V/AC24V Dual Power Input

## **OTHER FEATURES**

- DC12V Power Output
- Up the Coax Coaxitron Support
- AGC, 3D-DNR, BLC

## ANALOGUE HD TYPICAL CABLE DISTANCE



**DVR** 

	5MP	2MP	720P
COAX (RG59)	UP TO 500M	UP TO 500M	UP TO 500M
CAT5e	UP TO 200M	UP TO 305M	UP TO 350M
CAT6	UP TO 200M	UP TO 305M	UP TO 350M

 $^*$ Approximate distances calculated using HD MasterBaluns. Actual transmission range will vary depending on type and quality of cable and baluns.

CONCEPT PRO
AHD RECORDING
RANGE

## AIR8025EL-AHD5M-Z




Concept Pro 5MP 4-in-1 Analogue Motorised External Bullet Camera


## **SPECIFICATION**


Model/Fea	ature	AIR8025EL-AHD5M-Z	
	Image Sensor	1/2.8" Progressive Scan CMOS	
	Video Output Type	AHD/TVI/CVI/CVBS	
Camera	Signal System	PAL/NTSC	
	Min. Illumination	Colour: 0.03 lux (Enhanced Low Light) B&W: 0.003 lux (Enhanced Low Light) 0 lux with IR on	
	Electronic Shutter	Auto	
	S/N Ratio	≥50dB	
	IR LEDs	x8	
	IR Illumination Range	Max. 80m	
Lens	IR Control	On/Off	
	Adaptable IR	Auto	
	Pivot Axis	Pan: 0°–360°, Tilt: 0°–75°, Rotation: 0°–360°	
	Lens Type	Motorised	
		Built-in	
	Mount Type	f=2.7-13.5mm	
	Focal Length	F1.3-F2.7	
	Aperture	H: 108.78°-28.76°, V: 57.22°-16.2°, D: 130.54°-33°	
	Angle of View		
	Focus	Auto/Manual	
	Iris	Fixed	
	Resolution Frame Rate	5MP (2592x1944), 4MP (2560x1440), 2MP (1920 x 1080), SD (960 x 576 AHD/TVI: 12.5/20FPS @ 5MP, 15/25/30FPS @ 4MP, 25/30FPS @ 2MP CVI: 25/30FPS @ 4MP, 25/30FPS @ 2MP CVBS: 25/30FPS @ SD	
	Day/Night	True Day & Night with ICR (Auto/Colour/B&W/EXT)	
	Backlight Compensation	BLC/Global	
	Wide Dynamic Range	True WDR	
	White Balance	Pro/Gray World	
	Gain Control	Auto	
Video	Noise Reduction	3D-DNR (Auto/Manual)	
	Motion Detection	-	
	Defog		
	Image Setting	Mirror	
	Image Adjustment	Brightness, Sharpness, Contrast, Saturation	
		Brightness, Sharphess, Contrast, Saturation	
	Privacy Masking	•	
	Sens-Up	May 500m (4) (n n 750)	
Interface	Transmission Distance	Max. 500m (1Vp-p 75Ω)	
	Video Output	x1 1.0Vp-p 75Ω BNC/x1 2-pin UTP	
	Audio Interface	*	
	RS-485	-	
	Control Protocol	N/A	
	Up the Coax (Coaxitron) Support	Yes	
	OSD Buttons	Yes	
General	Power Supply	DC12V±10%/AC24V±10%	
	Power Output	x1 DC12V 100mA	
	Power Consumption	Max. 9W	
	Operating Temperature	-30°C to +50°C	
	Operating Humidity	20-80% RH	
	Ingress Protection	IP66	
	Impact Resistance	-	
	Housing Materials	Aluminum Diecasting	
	RAL	RAL 7021 Black Grey	
	Dimension	Ø86mm × (L) 270mm without sunshield	
	Net Weight	≈800g	
	Gross Weight	≈1,250g	


#### **DIMENSIONS**

#### All measurements are in mm.









## ORDER CODE

AIR8025EL-AHD5M-Z

Concept Pro 5MP 4-in-1 Analogue Motorised External Bullet Camera

## OTHER PRODUCTS IN THE RANGE

AIR8025EL-AHD2M-Z

Concept Pro Lite 2MP 4-in-1 Analogue Motorised External Bullet Camera

## RECOMMENDED ACCESSORIES

• CP-BASE-1-V2-G Concept Pro Small Junction Box - Black Grey
• CP-WM-1-V2-G Concept Pro Small Wall Mount - Black Grey

• CP-PM-1-V2-G Concept Pro Small Pendant Mount - Black Grey

 • CP-PLM-V2
 Concept Pro Pole Mount

 • CP-CM-V2
 Concept Pro Corner Mount

 • RG59K-100
 RG59 Coaxial Cable 100m (Black))

 • RG59K-500
 RG59 Coaxial Cable 500m (Black)

CONCEPT PRO
AHD RECORDING
RANGE

## AIR8025EL-AHD5M-Z



Concept Pro 5MP 4-in-1 Analogue Motorised External Bullet Camera

## ACCESSORIES DIMENSIONS

#### CP-BASE-1-V2-G


Concept Pro Small Junction Box












Concept Pro Small Pendant Mount





## CP-WM-1-V2-G

Concept Pro Small Wall Mount














## CP-PLM-V2

Concept Pro Pole Mount (can be combined with CP-BASE-1-V2)









#### CP-CM-V2

Concept Pro Corner Mount (can be combined with CP-BASE-1-V2)







COMPATIBLE WITH

