



5MP

2.8mm Fixed Lens 20M IR

4 in 1

CVP5325IREL-AHD5M/2.8

Concept Pro 5MP 4-in-1 Analogue Fixed Compact External Dome Camera

The CVP5325IREL-AHD5M/2.8 model is a 4-in-1 analogue camera that has been designed to deliver the highest image quality for demanding external environments. This weather-resistant compact external dome features a 2.8mm fixed lens, smart infrared LEDs with 20m illumination range, and provides crisp 5-megapixel video with true wide dynamic range and enhanced low light performance. This camera is also designed for excellent compatibility with the Concept Pro range of hybrid digital video recorders.



True Wide Dynamic Range

With true wide dynamic range, this camera can capture sharp images throughout the entire field of view, even when there are severe differences between light levels.



Enhanced Low Light

This CCTV camera utilises an Enhanced Low Light CMOS sensor with greater light sensitivity, resulting in the camera capturing colour images long after standard CCTV cameras have switched to black & white night mode.



DC12V Power Output

This CCTV camera also provides a DC12V 100mA power output that can be conveniently used to power some auxiliary equipment rather than using a separate power supply adapter.

KEY FEATURES

- Max. 20FPS @ 5MP
- 2.8mm Fixed Lens
- Up to 20m Smart IR Illumination
- 4-in-1 Operation (AHD/TVI/CVI/CVBS)
- Enhanced Low Light Performance
- True Wide Dynamic Range

OTHER FEATURES

- DC12V/AC24V Power Input
 & DC12V Power Output
- Up the Coax Coaxitron Support
- AGC, 3D-DNR, BLC
- ▶ IP66-rated

ANALOGUE HD TYPICAL CABLE DISTANCE



DVR

	5MP	2MP	720P
COAX (RG59)	UP TO 500M	UP TO 500M	UP TO 500M
CAT5e	UP TO 200M	UP TO 305M	UP TO 350M
CAT6	UP TO 200M	UP TO 305M	UP TO 350M

*Approximate distances calculated using HD MasterBaluns. Actual transmission range will vary depending on type and quality of cable and baluns.



CVP5325IREL-AHD5M/2.8

Concept Pro 5MP 4-in-1 AHD Fixed Lens Compact Vandal Dome Camera





SPECIFICATION


Model/Fea	ature	CVP5325IREL-AHD5M/2.8	
	Image Sensor	1/2.8" Progressive Scan CMOS	
	Video Output Type	AHD/TVI/CVI/CVBS	
	Signal System	PAL/NTSC	
	Min. Illumination	Colour: 0.4 lux (Enhanced Low Light)	
		B&W: 0.04 lux (Enhanced Low Light) 0 lux with IR on	
Camera	Electronic Shutter	Auto	
	S/N Ratio	≥50dB	
	IR LEDs	x4	
	IR Illumination Range	Max. 20m	
	IR Control	On/Off	
	Adaptable IR	Auto	
	Pivot Axis	Pan: 0-353°, Tilt: 0-70°, Rotation: 0-176°	
Lens	Lens Type	Fixed	
	Mount Type	Built-in	
	Focal Length	f=2.8mm	
	Aperture	F2.0	
	Angle of View	H: 104°, V: 76°, D: 112°	
	Focus	Fixed	
	Iris	Fixed	
	Resolution	5MP (2592x1944), 4MP (2560x1440), 2MP (1920 x 1080), SD (960 x 576	
	Frame Rate	AHD/TVI: 12.5/20FPS @ 5MP, 15/25/30FPS @ 4MP, 25/30FPS @ 2MP	
	Frame hate	CVI: 25/30FPS @ 4MP, 25/30FPS @ 2MP	
		CVBS: 25/30FPS @ SD	
	Day/Night	True Day & Night with ICR (Auto/Colour/B&W/EXT)	
	Backlight Compensation	BLC/Global	
	Wide Dynamic Range	True WDR	
	White Balance	Pro/Gray World	
Video	Gain Control	Auto	
video	Noise Reduction	3D-DNR (Auto/Manual)	
	Motion Detection	- Auto/Manual)	
	Defog	-	
		Mirror	
	Image Setting Image Adjustment	Brightness, Sharpness, Contrast, Saturation	
	Privacy Masking	Brightness, Sharphess, Contrast, Saturation	
	Sens-Up	<u> </u>	
		May 500m (4) (n n 750)	
	Transmission Distance	Max. 500m (1Vp-p 75Ω)	
	Video Output	x1 1.0Vp-p 75Ω BNC (AHD/TVI/CVI/CVBS) x1 2-pin UTP Video Output	
	Audia Interfesa	XT 2-piri OTP video Output	
Interface	Audio Interface	<u> </u>	
	RS-485	- N1/A	
	Control Protocol	N/A	
	Up the Coax (Coaxitron) Support	Yes	
	OSD Buttons	Yes	
General	Power Supply	DC12V±10%/AC24V±10%	
	Power Output	DC12V, Max. 100mA	
	Power Consumption	Max. 6.5W	
	Operating Temperature	-30°C to +40°C	
	Operating Humidity	20-80% RH	
	Ingress Protection	IP66	
	Impact Resistance	IK10	
	Housing Materials	Aluminum Diecasting	
	RAL	RAL 9010 Pure White	
	Dimension	Ø110.8×81.8mm	
	Net Weight	≈450g	
	Gross Weight	≈650g	
Certification	Certifications	CE	

DIMENSIONS

All measurements are in mm.







ORDER CODE

• CVP5325IREL-AHD5M/2.8

Concept Pro 5MP 4-in-1 Analogue Fixed Compact External Dome

OTHER PRODUCTS IN THE RANGE

• CVP5325IREL-AHD2M/2.8

Concept Pro Lite 2MP 4-in-1 Analogue Fixed Compact External Dome

RECOMMENDED ACCESSORIES

• CP-BASE-1-V2 • CP-WM-1-V2 • CP-PM-1-V2 • CP-TM-1-V2

• CP-PLM-V2 Cot • CP-CM-V2 Cot • CP-RC-V2 Cot • RG59K-100 RG • RG59K-500 RG

Concept Pro Small Junction Box Concept Pro Small Wall Mount Concept Pro Small Pendant Mount Concept Pro Small In-ceiling/Tile Mount Concept Pro Pole Mount Concept Pro Corner Mount

Concept Pro Rain Cap RG59 Coaxial Cable 100m (Black) RG59 Coaxial Cable 500m (Black)

CONCEPT PRO
AHD RECORDING
RANGE

CVP5325IREL-AHD2M/2.8

Concept Pro 5MP 4-in-1 AHD Fixed Lens Compact Vandal Dome Camera



ACCESSORIES

CP-TM-1-V2

Concept Pro Small In-ceiling/Tile Mount



DIMENSIONS







Concept Pro Small Junction Box










CP-PM-1-V2

Concept Pro Small Pendant Mount





CP-WM-1-V2

Concept Pro Small Wall Mount













CP-PLM-V2

Concept Pro Pole Mount (can be combined with CP-BASE-2-V2)








CP-CM-V2

Concept Pro Corner Mount (can be combined with CP-BASE-2-V2)







CP-RC-V2