DATASHEET



Concept 🚫 Pro



CVP9316IREL-AHD5M/2.8 CVP9316IREL-AHD5M-G/2.8

Concept Pro 5MP 4-in-1 Analogue Fixed Lens External Turret Camera

The CVP9316IREL-AHD5M/2.8 model is a 4-in-1 analogue camera that has been designed to deliver the highest image quality for demanding external environments. This weather-resistant external turret features a 2.8mm fixed lens, smart infrared LEDs with 30m illumination range, and provides crisp 5-megapixel video with true wide dynamic range and enhanced low light performance. This camera is also designed for excellent compatibility with the Concept Pro range of hybrid digital video recorders.



True Wide Dynamic Range

With true wide dynamic range, this camera can capture sharp images throughout the entire field of view, even when there are severe differences between light levels.



sensor with greater light sensitivity, resulting in the camera

Enhanced Low Light Performance

capturing colour images long after standard CCTV cameras have switched to black and white night mode.

This CCTV camera utilises an Enhanced Low Light CMOS



Four-in-one solution

Don't be tied down to any single analogue platform. With Concept Pro 4-in-1 cameras you have the freedom to install whichever CCTV platform you like, whether you install AHD, TVI, CVI, or traditional analogue systems.

ANALOGUE HD TYPICAL CABLE DISTANCE

Camera				
	5MP	2MP	720P	1
COAX (RG59)	UP TO 500M	UP TO 500M	UP TO 500M	1
CAT5e	UP TO 200M	UP TO 305M	UP TO 350M	
CAT6	UP TO 200M	UP TO 305M	UP TO 350M	1

*Approximate distances calculated using HD MasterBaluns.

Actual transmission range will vary depending on type and quality of cable and baluns.

KEY FEATURES

- Max. 20FPS @ 5MP
- 2.8mm Fixed Lens
- Up to 30m Smart IR Illumination
- 4-in-1 Operation (AHD/TVI/CVI/CVBS)
- Enhanced Low Light Performance
- True Wide Dynamic Range

OTHER FEATURES

- DC12V Power Input
- Up the Coax Coaxitron Support
- AGC, 3D-DNR, BLC
- IP66-rated



CVP9316IREL-AHD5M/2.8 CVP9316IREL-AHD5M-G/2.8





Concept Pro 5MP 4-in-1 Analogue Fixed Lens External Turret Camera

SPECIFICATION

Model/Fe		CVP9316IREL-AHD5M/2.8 CVP9316IREL-AHD5M-G/2.8		
	Image Sensor	1/2.8" Progressive Scan CMOS		
	Video Output Type	AHD/TVI/CVI/CVBS		
	Signal System	PAL/NTSC		
	Min. Illumination	Colour: 0.4 lux (Enhanced Low Light)		
		B&W: 0.04 lux (Enhanced Low Light)		
		0 lux with IR on		
Camera	Electronic Shutter	Auto		
	S/N Ratio	≥50dB		
	IR LEDs	x2		
	IR Illumination Range	Max. 30m		
	IR Control	On/Off		
	Adaptable IR	Auto		
	Pivot Axis	Pan: 0-349°, Tilt: 0-80°, Rotation: 0-360°		
Lens	Lens Type	Fixed		
	Mount Type	Built-in		
	Focal Length	f=2.8mm		
	Aperture	F2.0		
	Angle of View	H: 104°, V: 76°, D: 112°		
	Focus	Fixed		
	Iris	Fixed		
	Besolution	5MP (2592x1944), 4MP (2560x1440), 2MP (1920 x 1080), SD (960 x 576		
	Frame Bate	AHD/TVI: 12.5/20FPS @ 5MP. 15/25/30FPS @ 4MP. 25/30FPS @ 2MP		
	Traine nate	CVI: 25/30FPS @ 4MP, 25/30FPS @ 2MP		
		CVBS: 25/30FPS @ SD		
	Day/Night	True Day & Night with ICR (Auto/Colour/B&W/EXT)		
	Backlight Compensation	BLC/Global		
		True WDR		
	Wide Dynamic Range White Balance			
Video		Pro/Gray World		
	Gain Control	Auto		
	Noise Reduction	3D-DNR (Auto/Manual)		
	Motion Detection	-		
	Defog	-		
	Image Setting	Mirror		
	Image Adjustment	Brightness, Sharpness, Contrast, Saturation		
	Privacy Masking	-		
	Sens-Up	-		
	Transmission Distance	Max. 500m (1Vp-p 75Ω)		
Interface	Video Output	x1 1.0Vp-p 75Ω BNC (AHD/TVI/CVI/CVBS)		
	Audio Interface	-		
	RS-485	-		
Internace	Control Protocol	N/A		
	Up the Coax (Coaxitron) Support	Yes		
	OSD Buttons	Yes		
General	Power Supply	DC12V±10%		
	Power Output	-		
	Power Consumption	Max. 4.8W		
	Operating Temperature	-30°C to +40°C		
	Operating Humidity	20-80% RH		
	Ingress Protection	IP66		
	Impact Resistance	-		
	Housing Materials	- Aluminum Diecasting		
	RAI	CVP9316IREL-AHD5M/2.8: RAL 9010 Pure White		
	I VAL	CVP9316IREL-AHD5W/2.8: RAL 9010 Pure White CVP9316IREL-AHD5M-G/2.8: RAL 7021 Black Grey		
	Dimension			
		Ø120 x (H) 94.8mm		
	Net Weight	≈480g		
	Gross Weight	≈630g		

DIMENSIONS





ORDER CODE

- CVP9316IREL-AHD5M/2.8
- + CVP9316IREL-AHD5M-G/2.8

Concept Pro 5MP 4-in-1 Analogue Fixed External Turret Camera Concept Pro 5MP 4-in-1 Analogue Fixed External Turret Camera (Grey)

OTHER PRODUCTS IN THE RANGE

+ CVP9316IREL-AHD2M/2.8

Concept Pro Lite 2MP 4-in-1 Analogue Fixed External Turret Camera

RECOMMENDED ACCESSORIES

CP-BASE-1-V2

 CP-WM-1-V2 Concept Pro Small Wall Mount

- Concept Pro Small Junction Box Concept Pro Small Pendant Mount
- CP-PM-1-V2 Concept Pro Pole Mount
 - Concept Pro Corner Mount
- CP-PLM-V2 CP-CM-V2 • RG59K-100
- RG59 Coaxial Cable 100m (Black) RG59 Coaxial Cable 500m (Black)

• RG59K-500

COMPATIBLE WITH

CONCEPT PRO AHD RECORDING RANGE

CVP9316IREL-AHD5M/2.8 CVP9316IREL-AHD5M-G/2.8

Concept Pro 5MP 4-in-1 Analogue Fixed Lens External Turret Camera



