

Concept 🚫 Pro



# CVP9329IREL-AHD2M CVP9329IREL-AHD2M-G

Concept Pro Lite 2MP 4-in-1 Analogue Varifocal External Eyeball Camera

The CVP9329IREL-AHD2M model is a 4-in-1 analogue camera that has been designed to deliver the highest image quality for demanding external environments. This weather-resistant external eyeball features a varifocal lens, smart infrared LEDs with 30m illumination range, and provides crisp 2-megapixel video at real-time frame rates with true wide dynamic range and enhanced low light performance. This camera is also designed for excellent compatibility with the Concept Pro range of hybrid digital video recorders.



# True Wide Dynamic Range

With true wide dynamic range, this camera can capture sharp images throughout the entire field of view, even when there are severe differences between light levels.



# **Enhanced Low Light Performance**

This CCTV camera utilises an Enhanced Low Light CMOS sensor with greater light sensitivity, resulting in the camera capturing colour images long after standard CCTV cameras have switched to black and white night mode.



#### Four-in-one solution

Don't be tied down to any single analogue platform. With Concept Pro 4-in-1 cameras you have the freedom to install whichever CCTV platform you like, whether you install AHD, TVI, CVI, or traditional analogue systems.

# ANALOGUE HD TYPICAL CABLE DISTANCE

lera				C
	5MP	2MP	720P	]
COAX (RG59)	UP TO 500M	UP TO 500M	UP TO 500M	
CAT5e	UP TO 200M	UP TO 305M	UP TO 350M	
CAT6	UP TO 200M	UP TO 305M	UP TO 350M	

\*Approximate distances calculated using HD MasterBaluns. Actual transmission range will vary depending on type and quality of cable and baluns.

# **KEY FEATURES**

- Max. 25FPS @ 2MP
- 2.8-12mm Varifocal Lens
- Up to 30m Smart IR Illumination
- 4-in-1 Operation (AHD/TVI/CVI/CVBS)
- Enhanced Low Light Performance
- True Wide Dynamic Range

# **OTHER FEATURES**

- DC12V/AC24V Dual Power Input
- Up the Coax Coaxitron Support
- AGC, Sens-up, AWB, BLC, HLC
- IP66-rated



# CVP9329IREL-AHD2M CVP9329IREL-AHD2M-G

Concept Pro Lite 2MP 4-in-1 Analogue Varifocal External Eyeball Camera


### SPECIFICATION

Model/Fea	ature	CVP9329IREL-AHD2M / CVP9329IREL-AHD2M-G		
	Image Sensor	1/2.8" Progressive Scan CMOS		
Camera	Video Output Type	AHD/TVI/CVI/CVBS		
	Signal System	PAL/NTSC		
	Min. Illumination	Colour: 0.02 lux (Enhanced Low Light) B&W: 0.002 lux (Enhanced Low Light) 0 lux with IR on		
	Electronic Shutter	Auto/Manual, 1/25–1/25,600s		
	S/N Ratio	≥50dB		
	IR LEDs	x4		
	IR Illumination Range	Max. 30m		
	IR Control	On/Off		
	Adaptable IR	Auto		
	Pivot Axis	Pan: 0-349°, Tilt: 0-80°, Rotation: 0-360°		
	Lens Type	Manual Varifocal		
	Mount Type	Built-in		
	Focal Length	f=2.8-12mm		
	Aperture	F1.8		
	Angle of View	H: 95-27°, V: 67-19°, D: 135-35°		
	Focus	Manual		
	Iris	Fixed		
	Resolution	2MP (1920 x 1080), SD (960 x 576)		
		AHD/TVI/CVI: 25/30FPS @ 2MP		
	Frame Rate	CVBS: 25/30FPS @ SD		
	Day/Night	True Day & Night with ICR (Auto/Colour/B&W/EXT)		
	Backlight Compensation	BLC/HLC		
Video	Wide Dynamic Range	True WDR		
	White Balance	Auto/AutoExt/Preset/Manual		
	Gain Control	Auto (AGC, 0–20)		
	Noise Reduction	2D/3D-DNR (High/Middle/Low/Off)		
	Motion Detection	Yes		
	Defog	-		
	Image Setting	Freeze, Flip		
	Image Adjustment	Brightness, Sharpness, Colour Gain, Ace, Gamma		
	Privacy Masking	Yes		
	Sens-Up	Yes (x2/x4/x8/x16/x32/Off)		
	Transmission Distance	Max. 500m (1Vp-p 75Ω)		
Interface	Video Output	x1 1.0Vp-p 75Ω BNC (AHD/TVI/CVI/CVBS)		
	Audio Interface	-		
	RS-485			
	Control Protocol	N/A		
	Up the Coax (Coaxitron) Support	Yes		
	OSD Buttons	Yes		
	Power Supply	DC12V±10%/AC24V±10%		
General	Power Output	-		
	Power Consumption	 Max. 4.8W		
	Operating Temperature	-30°C to +50°C		
	Operating Humidity	20-80% RH		
	Ingress Protection	IP66		
		IFUU		
	Impact Resistance	- Aluminum Disconting		
	Housing Materials	Aluminum Diecasting		
	RAL	CVP9329IREL-AHD2M: RAL 9010 Pure White CVP9329IREL-AHD2M-G: RAL 7021 Black Grey		
	Dimension	Ø120 x (H) 105.5mm		
	Net Weight	≈500g		
	Gross Weight	≈650g		
	Certifications	CE		

# Concept 🚫 Pro

# DIMENSIONS

#### All measurements are in mm.



#### ORDER CODE

CVP9329IREL-AHD2M
 CVP9329IREL-AHD2M-G

Concept Pro Lite 2MP 4-in-1 Analogue Varifocal External Eyeball Camera Concept Pro Lite 2MP 4-in-1 Analogue Varifocal External Eyeball Camera (Black-Grey)

#### OTHER PRODUCTS IN THE RANGE

CVP9329IREL-AHD5M
 CVP9329IREL-AHD5M-G

Concept Pro 5MP 4-in-1 Analogue Varifocal External Eyeball Camera Concept Pro 5MP 4-in-1 Analogue Varifocal External Eyeball Camera (Black Grey)

#### RECOMMENDED ACCESSORIES

<ul> <li>CP-BASE-1-V2</li> </ul>
----------------------------------

- CP-BASE-1-V2-G
- + CP-WM-1-V2
- CP-WM-1-V2-G
   CP-PM-1-V2
- CP-PM-1-V2-G
- + CP-PLM-V2
- + CP-CM-V2
- RG59K-100
- RG59K-500

Concept Pro Pole Mount Concept Pro Corner Mount RG59 Coaxial Cable 100m (Black))

RG59 Coaxial Cable 500m (Black)

Concept Pro Small Junction Box

Concept Pro Small Wall Mount

Concept Pro Small Pendant Mount

Concept Pro Small Junction Box - Black Grey

Concept Pro Small Wall Mount - Black Grey

Concept Pro Small Pendant Mount - Black Grey

COMPATIBLE WITH

CONCEPT PRO AHD RECORDING RANGE

# CVP9329IREL-AHD2M CVP9329IREL-AHD2M-G

Concept Pro Lite 2MP 4-in-1 Analogue Varifocal External Eyeball Camera

# ACCESSORIES

CP-BASE-1-V2 CP-BASE-1-V2-G Concept Pro Small

Concept Pro Small Junction Box



# CP-PM-1-V2 CP-PM-1-V2-G

Concept Pro Small Pendant Mount



CP-WM-1-V2 CP-WM-1-V2-G

Concept Pro Small Wall Mount



# CP-PLM-V2

Concept Pro Pole Mount (can be combined with CP-BASE-1-V2)

# CP-CM-V2

Concept Pro Corner Mount (can be combined with CP-BASE-1-V2)





# DIMENSIONS

