Concept Pro



8MP

4K Display Output

H.265

x2/x1 Alarm I/O






VUHDIPL-8-2

Concept Pro Lite 8 Channel 8MP NVR with PoE

The VUHDIPL-8-2 model is an eight channel network video recorder designed to satisfy most entry-level to professional requirements. It has eight channels of PoE/PoE+ built-in, supports the latest H.265 video compression codec for greater storage and bandwidth savings, and provides real-time recording performance at up to 8-megapixel resolutions across all channels.



Professional Remote Monitoring

Provides 24 hour remote monitoring for clients and is available on all Concept Pro recorders with Alarm Receiving Stations using Immix Cloud and Sentinel platforms.



Deep Learning Video Analytics

This product supports the latest Deep Learning video analytics technology when compatible Concept Pro IP cameras are connected. Easily configure Deep Learning Motion Detection and advanced video analytics rules from the recorder user interface and begin reducing false alarms by up to 95% with the power of Deep Learning.



NDAA Compliant

This product uses the latest in chipset technology from Taiwan and is developed in South Korea without the use of restricted components.



Enhanced Security

This product supports a suite of security-related features, including automatic password expiration, encryption, and more settings designed to ensure authorised users are accessing the device.

KEY FEATURES

- 8 PoE/PoE+ IP Camera Inputs
- H.265 & H.264 Video Codec Support
- Real-time 8MP Recording for all Channels
- Max. 3840x2160 4K UHD Display Output
- Up to 20TB Internal Hard Disk Capacity
- Smart Storage Compression
- Audio Recording & HDMI Audio Out
- x2/x1 Alarm I/O
- Compatible with Concept Pro Deep Learning Video Analytics
- WD Purple Surveillance Hard Disks Preinstalled

OTHER FEATURES

- NDAA-compliant
- Remote Monitoring via Concept Pro Viewer Mobile App
- Supported by i-PIMS license-free VMS
- Timeline, Thumbnail, Event, and Deep Learning Search Modes
- Instant Playback
- Integrated Virtual Alarm Support
- Mouse and remote included
- Total 180W PoE Capacity






SPECIFICATION


Fire Processing Processing Processing Processing Processing	Video and Audio		Event	
Man Surject Man Capable Max 2500FPS 9500D SURF FK UPD per chains Man Description Man Descrip		x8	Alarm Inputs	x2 (NVR) + x8 (IP Camera)
Max. 2007/cition/from Retail			Alarm Outputs	
Machine Mach			·	Alarm Recording, Alarm Output, PTZ Preset, E-mail/Mobile
Paced Paced Browning Code Systems (1997-1997) (1997-1997-1997-1997-1997-1997-1997-1997	Video Compression Codec			
Bit Rate per Chromal Stream 11 2004-2005/090 Prover one Filternal (PuP) Provided Published Pu	Incoming Bandwidth			Supported (Depending on IP Camera Specification)
Bernard per Channel Steman # 11,000 & 0,000 pps Steman # 10,000 & 0,000 pps Provided Plannel PGD Provided PCP Command PCP Command PCP Command Max_CVV per command Max_CVV per command PCP Command Max_CVV per	Bit Rate Control		Deep Learning Motion	Supported (Salact Concept Pro ID Camera Models)
Power of Ehrmel (PG) Post Service Post Servic	Dit Data was Observed			Supported (Select Concept Fro IF Carriera Models)
Post Sandred Post Durpted Miss. 2009 per channel Note: International Post Post Selection (Post Post Post Post Post Post Post Post	Bit Rate per Channel	Stream 2: 600-2,000Kbps	DL Motion Detection	Human/Car/Rike
PRE OUTUAL MAX. 1809 for cannel MAX. 1809 for cannel MAX. 1809 for cannel MAX. 1809 for cannel Supported. Network-PSE49 for will fill come. Supported. Acid or prox.	Power over Ethernet (PoE)	V0	Objects	
De Signatural PM 1972-2012-2013 No. 15. 1972-2013-2014 No. 15. 1972-2013-2014 No. 15. 1972-2014 No. 15	Inputs	Xδ	Motion Event Triggers	
PAPE Commens. Supported, Nativork (1985) Sprill (2020m), Sp	PoE Standard	PoE 802.3af/802.3at		
System Fever Types System Fever	BoE Output	Max. 25W per channel		
PTZ Carrenas New York Audio Audio Didute Audio Didute New York Audio Audio Carrenas Audio Carrenas New York Audio Audio Carrenas Audio Carrenas New York Audio Audio Ca	FOL Output		System Event Types	
POSATA M Feerls POSATA M Feerls Posata M Feerls Posata M Fe	DT7 Comoros	Supported, Network/RS485 (Pan/Tilt/Zoom, Scan, Tour,	- Oystern Event Types	
Deep Learning Potents Audio Compression Code Audio C				
Two-way Audio Audio Compression Codes G.7.11 Naw Procuring Pedeution May Gashard StaySay May Pay M				
Deep Learning Rule Types Deep Learning Rule		x1 (HDMI)	Deep Learning Events	
Deep Learning Not replaced proceeding Passe Using Passeution Max. 2012/01/PIS & 394/02/1018/MP/CIT/CIF Paccording Notes Max. 2012/01/PIS & 394/02/1018 (BMP 4K UHI) Deep Learning Learning Libert Immeliate Max Controlled Passeution Deep Learning Libert Immeliate Supported Deep Learning Libert Immeliate Supported Deep Learning Libert Immeliate Supported Deep Learning Libert Immeliate Deep Learning Libert Immeliat		-	Deep Learning Objects	
Becording Pacountion But P CASIN-D 1950/HAMP CARP/SAMP/SAMP/SAMP/SAMP/SAMP/SAMP/SAMP/SAM		G.711µ-law	Deep Learning Rule Types	
Deep Learning Execution Mode Continuous, Motion, Deep Learning Platms, Paris Mode Peccurity Mode Continuous, Motion, Deep Learning Platms, Paris Mode Peccurity Proceedings Procedings Proceedings Proceedings Proceedings Procedings Procedings Proceedings Proceedings Procedings Procedings Proceedings Procedings Procedings Procedings Procedings Proceedings Procedings P				
Recording Modes Continuous, Motor, Despot Jeaning Pollifes with Peccenting Scheduling Preceived Recording Yes, 07/23/4/570/158 Prot. Fuerri Recording Yes, 07/23/4/570/158 Supported Suppo				
Recording Modes Continuous, Motion, Deep Learning/Alarm, Paine Modes Recording Modes Per-Event Recording Yes, 07/28/34/87/1016s Per-Event Recording Yes, 10/28/34/87/1016s Per-Event Recording Yes, 10/28/34/87/1016s Per-Event Recording Yes, 10/28/34/87/1016s Per-Event Recording Per-Event Recording Yes, 10/28/34/87/1016s Per-Event Recording Yes, 10/28/34/97/1016s Per-Event Recording Yes, 10/28/34/97/1016s Per-Ev	Recording Rate			
Supported Suppor	Recording Modes			E-mail Notification, FTP Notification, Mobile App Push Message
Placetrit Recording Yes, 617015/00.0001696 Pool Foed Peconding Yes, 617015/00.0001696 Supported Supported Supported Supported Supported Supported Main Display Outputs HDMLx1, VGA x1 Display Placetrition Supported Main Display Outputs Supported Supported Supported Main Display Outputs Supported Supported Main Display Memory M				Supported
Post-Event Recording Yes, 6/10/15/20/30/60/1808 Supported Storage Compression Supported Storage Compression Supported Storage Supported Supporte				· ·
Signary Strategy Compression (SSC) Bisplay Man Display Outputs Begin Agency Compression (SSC) Bisplay Man Display Outputs Begin Agency Compression (SSC) Bisplay Man Display Outputs Baddorf (1907-6660x1446/1920x1486/1280x124/1280x720) Autported (Man Display Memoring Datal Monitor Functionally) Man Display Memoring Baddorf (1907-660x1446/1920x1486/1280x124/1280x720) Autported (1907-1926) Baddorf (1907-1926) Baddo				
Display Disp		Yes, 5/10/15/20/30/60/180s		
Display Disp	Ŭ i	Supported		Supported
Mear Discray Outputs		.,		SATA v2 May 20TB
Despits Configuration Selection Selection Selection Supported Dual Monitor Functionality Main Display Mirroring Parlial Detail Despits Configuration Supported Support		LIDMING VCA vd		
Designation		DDIVILX I , VGA X I		
Dual Monitor Functionality Mair Display Memoring Display Decoding Rate Max. 2002/240FPS, Max. 60FPS48MP Programmable Sequence Supported. 1CH/4GH5GH6CH9GH Spott Monitor Output Spott Monitor Modes Calendar (Date/Time), Timeline, Thumbnall, Event, Text-in [POS), Deep Learning (POS), D			- TV IID COINIGUIATION	TVO, picase see Volibli E model
Display Decoding Rate Max. 2007/49FPS; Max. 60FPS@MAP Spit Screen Mode			Partial Data Deletion	Supported
Externed Storage Support Externed Storage Support Externed Storage Support			- artial Data Deletion	Supported
Programmable Sequence Supported, 1CH4QHSCH/9CH Spot Monitor Output Enhanced Security Pules Supported, enabled by default Spot Monitor Mode N/A Spot Monitor Mode N/A Supported, configurable by user and group authority Spot Monitor Mode Calendar (Date/Time). Timeline, Thumbnail, Event, Text-in (PCS), Deep Learning (PCS), Deep Learning Supported (Select Concept Pro I/P Camera Models Supported Search, Archiving, System Setup, Record Setup, Event Actio Control, Listen to Audio, Microphone, Remote Login, PTZ Control, Shutdown Unrequired network protocols of thy default, ShMMF FTP, DDN PSP, etc.), RTSP encryption (SEED, 128), HTTPS Digest, IP fills Network Security Network Security PSP, etc.), RTSP encryption (SEED, 128), HTTPS Digest, IP fills Network Security Network Security System Securit			External Storage Support	ETD (Rackup)
Spot Monitor Output N/A				ΤΠ (Βασκάβ)
Sport Morter Mode N/A Search & Pullyabek Search Modes Calendar (Date/Time). Timeline, Thimbrial, Event, Text-in (PCS), Deep Learning (PCS), Deep L				Supported, enabled by default
Search Modes Calendar (Date/Time), Timeline, Thumbnail, Event, Taxt-in (POS), Deep Learning (POS), Deep Learni		N/Δ		
Search Modes Calendar (Date/Time), Timeline, Thumbnal, Event, Tarching (POS), Deep Learning (POS), Deep Learni		1 4/7 3		
Event Search Options Event System, Network, Setup, Motion, Record, Storage, IPCAM, POS/ATM Deep Learning Search Options Event Type, Object/Keyword Dyplons Event Type, Object/Keyword Event Type, Object/Keyword Dyplons Event Type, Object/Keyword Event Type, Object/Keyword Dyplons Event Type, Object/Keyword Event Type, Object/Keyword Event Type, Object/Keyword Dyplons Event Type, Object/Keyword Event Pype, Object/Event Action Event Pype, Object/Reyword Event Pype, Object/Event Action Event Chives, Event Action Event Action Event Pype, Object/Event Action Event Chives, Event Action Event Chives, Interest Event Action Event Ch		Calendar (Date/Time) Timeline Thumbnail Event Text-in		
Event Search Options Alarm, Video, System, Network, Seup, Motion, Record, Storage, IPCAM, POS/ATM Deep Learning Search Options Event Type, Object/Keyword Options Deep Learning Search Options Event Type, Object/Keyword Options Event Type, Object/Keyword Options Deep Learning Search Options Deep Learning Search Options Event Type, Object/Keyword Options Deep Learning Search Options Deep Learning Search Options Event Type, Object/Keyword Options Deep Learning Search Dee	Search Modes			
Event Search Options Siorage, IPCAM, POS/ATM Deep Learning Search Options Event Type, Object/Keyword Options Max_200/Edyalops Event Mobile App Archive File Size Max_20GB Backup Encyption Backup Export Backup Encyption Backup Encyption Backup Encyption Backup Export Backup Encyption Backup English Description Backup Encyption Backup Encypt	- · · · · · · · · · · · ·			Search, Archiving, System Setup, Record Setup, Event Action
Deep Learning Search Event Type, Object/Keyword Options Event Type, Object/Keyword Options Event Type, Object/Keyword Options Event Type, Object/Keyword Options Event Type, Object/Keyword Uhrequired network protocols of fly default (SNMP, FTP, DDN P2P, etc.), RTSP encryption (SEED_128), HTTPS Digest, IP filts	Event Search Options		Group Authority	
Display Disp	Deep Learning Search			
Spit Screen Mode		Event Type, Object/Keyword		Unrequired network protocols off by default (SNMP, FTP, DDNS,
Spit Screen Mode 1/CH/4/CH/SCHYSCHYSCH CHYSCHYSCH SCH Chysche Speed 1/CH/4/CH/SCHYSCHYSCH SCH Chysche Speed 1/CH/4/CH/SCHYSCH SCH Chysche Speed 1/CH/4/CH/SCHYSCHYSCH Chysche Speed 1/CH/4/CH/SCHYSCH SCH Chysche Speed 1/CH/4/CH/SCHYSCH Chysche Speed 1/CH/4/CH/SCHYSCH Chysche Speed 1/CH/4/CH/SCHYSCH Chysche Speed 1/CH/4/CH/SCHYSCH/SCH Chysche Speed 1/CH/4/CH/SCHYSCH Chy	Playback Decoding Rate	Max. 200/240FPS; Max. 60FPS@8MP	Natural Caranit	P2P, etc.), RTSP encryption (SEED_128), HTTPS Digest, IP filter,
Required ADMIN password change, password recovery e-ma authentication, enhanced user ID/password on by default, dire user ID input on by default, and the collection, and recording by default, auto logout, password on by default, and or by default, auto logout, password on by default, auto logout, password o	Split Screen Mode	1CH/4CH/5CH/6CH/9CH	Network Security	Netstat, Ping test, IP conflict list, Live connected clients list with
Archiving Archiving Devices Archiving Devices Bemote Archiving Web, I-PIMS (PC), FTP, Concept Pro Viewer Mobile App Archived Video Format Archived Video Format Archive File Size Max. 20GB Backup Encryption MD5 with Built-in Verification Watermark Snapshot Bookmarking Bookmarking Bookmarking Boseward Data Management Supported Network Network Network Interface Max. 28 J45 10/100/1000M Ethernet Max. User Connections Transmission Rate Adaptive Network Streaming Outgoing Bandwidth Max. 72Mbps Max. 27 Supported Dual SMTP E-mail Server Remote Web Access Mobile App Concept Pro Viewer (IoS/Android) PC Software PEPC loud Service Yes, European Servers DNNS Fervice Yes, European Servers DNNS Froilies, SMTP PTRIES SMC Notification, enhanced user (Io/password on by default, autio logout, password expiration, system log, use authority, password expirati	Playback Speed	1x/2x/4x/8x/16x/32x/64x		lockout, Auto Port Forwarding off by default
Archiving Devices Archiving Devices Permote Archiving Archiving Devices Permote Archiving Archived Video Format Archived Video Format Archive File Size Archived File Size Archive File Size Archive File Size Archive File Size Backup Encryption MD5 with Built-in Verification Watermark Snapshot Bookmarking B	Ouick Playback	Ves via Live Menu Timeline or Quick Menu		Required ADMIN password change, password recovery e-mail
Archiving Devices Remote Archiving Archiving Devices Remote Web, i-PIMS (PC), FTP, Concept Pro Viewer Mobile App Archived Video Format RAW/AVI Archived Video Format RAW/AVI Archive File Size Max. 20GB Backup Encryption MD5 with Built-in Verification Watermark Snapshot Live, Playback (JPEG) Bookmarking Reserved Data Management Network Network Network Interface X2 RJ45 10/100/1000M Ethernet Max. 200/240FPS Adaptive Network Streaming Outgoing Bandwidth IP Address Supported New David Supported Nax. 72/Mbps IP Address Support Internet Explorer: Live Video, Search, Playback, Setup Chrome, Firefox: Live JPEG, Setup DDNS Service DDNS Service Yes, European Servers DDNS Service Yes, DVAILINK Included Remote Monitoring Interpreability Network, MSD, Piece SMTP, NTP, HTTP, FTP, Piece System Security System Security System Security System Security by default, audio transmission and recording of by default, audio anthorision by default, audio transmission and recording on the py default, audio anthorision by default, audio anthorision by default, audio anthorisy anthorision, anthorision wathorision wathorisis withorisited by default, audio anthorisited by default, audio anthorisited, auditorisited, by default, audio anthorisited, auditorisited, auditorisited, auditorisited, by default, auditorisited, auditorisited, auditorisited, a		Too, via Elve World Timoline of Quick World		
Remote Archiving Devices Web, i-PIMS (PC), FTP, Concept Pro Viewer Mobile App Archived Video Format RAW/AVI Archived Video Format RAW/AVI RAW/Besseved Data Management, Everybeta Settings File Import Export orisk management, Everybeta Settings File Import Export Settings File Import Export Settings File Import Export Settings File Import Export Settings File Import Settings Fil	A 111 D 1	LICE ETP		user ID input on by default, audio transmission and recording off
Archive Video Format Archive File Size Archive File Size Backup Encryption Backup Encryption Bookmarking Reserved Data Management Supported Max. 20GB Reserved Data Management Supported Max. 20GB Bookmarking Reserved Data Management Supported Supported Max. 20GB Bookmarking Reserved Data Management Supported Reserved Data Management Supported Max. 20GB Reserved Data Management Supported Reserved Data Management Supported Max. 20GB Reserved Data Management Supported Reserved Data Management Supported Reserved Data Management Supported Max. 20GB Supported Reserved Data Management Supported Resorver Remote Controller Reserved Controller Resorver Controller	Ü		System Security	by default, auto logout, password expiration, system log, user
Archive File Size Backup Encryption MDS with Built-in Verification Watermark Snapshot Live, Playback (JPEG) Bookmarking Reserved Data Management Supported Network Interface Max. User Connections Transmission Rate Adaptive Network Streaming Outgoing Bandwidth Dual SMTP E-mail Server Remote Web Access Internet Explorer: Live Vicleo, Search, Playback, Setup Chrome, Firefox: Live JPEG, Setup DDNS Service DDNS Service Pemote Monitoring Internet Explorers WS-Discovery, RTP, RTSP, RTCP, SMTP, NTP, HTTP, FTP, Concept Pro Vision Water Not Possible Available A			. ,	authority, password check for search/backup, password check
Backup Encryption MD5 with Built-in Verification Watermark Snapshot Live, Playback (JPEG) Bookmarking Supported Bookmarking Bookmarking Supported Bookmarking Bookmarking Supported Bookmarking Bookmark				for disk management, Encrypted System Settings File Import/
Interface Snapshot Live, Playback (JPEG) Bookmarking Supported Supported Supported Supported Se-485 x1 (Pelco-D, Pelco-P, D-max, etc.)				
Bookmarking Supported Supp	1 71		Interface	
Reserved Data Management Network Network Interface Max. User Connections Transmission Rate Adaptive Network Streaming Outgoing Bandwidth IP Address Supported Dual SMTP E-mail Server Remote Web Access Internet Explorer: Live Video, Search, Playback, Setup Chrome, Firefox: Live JPEG, Setup PC Software P2P Cloud Service DDNS Service Remote Monitoring Internet Max. 10/100/1000M Ethernet X2 RJ45 10/100/1000M Ethernet X2 RJ45 10/100/1000M Ethernet X2 RJ45 10/100/1000M Ethernet X2 RJ45 10/100/1000M Ethernet X4 Remote Control RS-232 System Language English, Spanish, German, French, Dutch, Italian, Korean, Chinese, Japanese, Polish Max. UTP Transmission P0 Max. UTP Transmission Firmware Upgrade USB, Network Operating System Concept Pro User Interface, NDAA-compliant SoC General Power Supply SMPS 51V/200W Power Consumption Max. 16W without HDD or cameras Fan X1 Dimensions 1U, (W) 380mm x (D) 314.6mm x (H) 44mm Rack Mount Supported Network Streaming Nover Consumption RS-232 System Language Chinese, Japanese, Polish Max. UTP Transmission Firmware Upgrade USB, Network Operating System Concept Pro User Interface, NDAA-compliant SoC General Power Consumption Fan Tims, Monitorsoft Sentinel Interoperability NoNIF Profile S, HTTP/RTSP SDK WS-Discovery, RTP, RTSP, RTCP, SMTP, NTP, HTTP, FTP. Certifications CF ECC.				x2 (Front)
Network Network Interface				
Network Interface x2 RJ45 10/100/1000M Ethernet Max. User Connections x10 Transmission Rate Max. 200/240FPS Adaptive Network Streaming Outgoing Bandwidth Max. 72Mbps IP Address Support IPv4, IPv6 Dual SMTP E-mail Server Supported Chrome, Firefox: Live Video, Search, Playback, Setup Chrome, Firefox: Live JPEG, Setup Mobile App Concept Pro Viewer (IOS/Android) PC Software I-PIMS OMS P2P Cloud Service Yes, European Servers DDNS Service Yes, DVRLINK Included Remote Monitoring Immix, Monitorsoft Sentinel Interoperability ONVIF Profile S, HTTP/RTSP SDK WS-Discovery, RTP, RTSP, RTCP, SMTP, NTP, HTTP, FTP, Concept Pro Service Supported		Сарроной	Keyboard Controller	
Max. User Connections Transmission Rate Adaptive Network Streaming Outgoing Bandwidth IP Address Support Dual SMTP E-mail Server Remote Web Access Mobile App Concept Pro Viewer (iOS/Android) PC Software P2P Cloud Service P2P Cloud Service Remote Monitoring Internet Explorers Support DDNS Service Remote Monitoring Internet Explorers Server DONNIE Profile S, HTTP/RTSP SDK DIMERITARIAN SERVER Max. 200/240FPS Adaptive Network Streaming Supported Max. 200/240FPS Language English, Spanish, German, French, Dutch, Italian, Korean, Chinese, Japanese, Polish Max. UTP Transmission Firmware Upgrade USB, Network Operating System Concept Pro User Interface, NDAA-compliant SoC General Power Supply Power Consumption Fan Dimensions 1U, (W) 380mm x (D) 314.6mm x (H) 44mm Rack Mount Net Weight Operating Conditions O°C to +40°C, 10%-90% Humidity (NC) Certifications CE FCC		v2 P I//5 10/100/1000M Etharnat		
Transmission Rate Adaptive Network Streaming Outgoing Bandwidth IP Address Support Dual SMTP E-mail Server Remote Web Access Mobile App Concept Pro Viewer (iOS/Android) PC Software P2P Cloud Service P2P Cloud Service Remote Monitoring Internet Explorers: Live John Service Remote Monitoring Internet Explorers: Live Video, Search, Playback, Setup DDNS Service Remote Monitoring Internet Explorers: Live John Service Remote Web Access Chrome, Firefox: Live John Service Chrome, Firefox: Live John Service Remote Web Access Chrome, Firefox: Live John Service Chrome, Firefox: Live John Service Remote Web Access				-
Adaptive Network Streaming Outgoing Bandwidth Max. 72Mbps IP Address Support Dual SMTP E-mail Server Remote Web Access Mobile App Concept Pro Viewer (iOS/Android) PC Software P2P Cloud Service Remote Monitoring Internet Explorers Ure Video, Search, Playback, Setup Chrome, Firefox: Live JPEG, Setup POWS Service Remote Monitoring Internet Explorers Ure Video, Search, Playback, Setup Chrome, Firefox: Live JPEG, Setup Concept Pro Viewer (iOS/Android) PC Software I-PIMS CMS P2P Cloud Service Yes, European Servers DDNS Service Remote Monitoring Interoperability ONVIF Profile S, HTTP/RTSP SDK Operating System Language Language Language Language Language Language Language Language Language Longuage Max. UTP Transmission Firmware Upgrade Operating System Concept Pro User Interface, NDAA-compliant SoC General Power Supply Power Consumption Max. 16W without HDD or cameras Fan Dimensions 1U, (W) 380mm x (D) 314.6mm x (H) 44mm Rack Mount Supported Net Weight Operating Conditions O°C to +40°C, 10%-99% Humidity (NC) Certifications CE FCC.				
Outgoing Bandwidth IP Address Support IP Address Support Dual SMTP E-mail Server Remote Web Access Internet Explorer: Live Video, Search, Playback, Setup Chrome, Firefox: Live JPEG, Setup Mobile App Concept Pro Viewer (iOS/Android) PC Software P2P Cloud Service PDNS Service Remote Monitoring Internet Explorers: Live JPEG, Setup DONS Service Remote Monitoring Internet Explorers: Live JPEG, Setup Chrome, Firefox: Live JPEG, Setup Chrome, Firefox: Live JPEG, Setup Concept Pro Viewer (iOS/Android) Power Supply SMPS 51V/200W Power Consumption Max. 1GW without HDD or cameras Fan Dimensions 1U, (W) 380mm x (D) 314.6mm x (H) 44mm Rack Mount Supported Net Weight Departing Conditions O°C to +40°C, 10%-90% Humidity (NC) Certifications CF ECC.				
IP Address Support Dual SMTP E-mail Server Remote Web Access Internet Explorer: Live Video, Search, Playback, Setup Chrome, Firefox: Live JPEG, Setup Mobile App Concept Pro Viewer (iOS/Android) PC Software P2P Cloud Service DDNS Service DDNS Service Semote Monitoring Internet Explorer: Live Video, Search, Playback, Setup Chrome, Firefox: Live JPEG, Setup Mobile App Concept Pro Viewer (iOS/Android) Power Supply SMPS 51V/200W Power Consumption Max. 16W without HDD or cameras Fan x1 Dimensions 1U, (W) 380mm x (D) 314.6mm x (H) 44mm Rack Mount Supported Net Weight Departing Conditions O°C to +40°C, 10%-90% Humidity (NC) Certifications Certifications Certifications Max. UP Iransmission Firmware Upgrade USB, Network Operating System Concept Pro User Interface, NDAA-compliant SoC General Power Supply Nax. UP Iransmission Firmware Upgrade USB, Network Operating System Concept Pro User Interface, NDAA-compliant SoC General Power Supply Nax. 16W without HDD or cameras Fan 1U, (W) 380mm x (D) 314.6mm x (H) 44mm Rack Mount Net Weight Operating Conditions O°C to +40°C, 10%-90% Humidity (NC) Certifications Certifications				Chinese, Japanese, Polish
Dual SMTP E-mail Server Remote Web Access Internet Explorer: Live Video, Search, Playback, Setup Chrome, Firefox: Live JPEG, Setup Mobile App Concept Pro Viewer (iOS/Android) PC Software P2P Cloud Service DDNS Service PService Service Pemote Web Access Internet Explorer: Live Video, Search, Playback, Setup Chrome, Firefox: Live JPEG, Setup Power Supply Power Supply Power Consumption Max. 16W without HDD or cameras Fan St Dimensions 1U, (W) 380mm x (D) 314.6mm x (H) 44mm Pack Mount Supported Net Weight Net Weight Net Weight Operating Conditions O°C to +40°C, 10%-90% Humidity (NC) Certifications Certifications Certifications Concept Pro User Interface, NDAA-compliant SoC Concept Pro User Interface, NDAA-compliant SoC Operating System Concept Pro User In				
Remote Web Access Internet Explorer: Live Video, Search, Playback, Setup Chrome, Firefox: Live JPEG, Setup Mobile App Concept Pro Viewer (iOS/Android) PC Software P2P Cloud Service DDNS Service DDNS Service Servic				
Mobile App Concept Pro Viewer (iOS/Android) PC Software i-PIMS CMS P2P Cloud Service Yes, European Servers DDNS Service Yes, DVRLINK Included Remote Monitoring Immix, Monitorsoft Sentinel Interoperability ONVIF Profile S, HTTP/RTSP SDK Overseted Petersels Chrome, Firefox: Live JPEG, Setup Power Supply Power Supply Power Supply Power Consumption Max. 16W without HDD or cameras Fan Dimensions 1U, (W) 380mm x (D) 314.6mm x (H) 44mm Rack Mount Supported Net Weight Operating Conditions O°C to +40°C, 10%-90% Humidity (NC) Certifications CE FCC				Concept Pro User Interface, NDAA-compliant SoC
Mobile App Concept Pro Viewer (iOS/Android) PC Software i-PIMS CMS P2P Cloud Service Yes, European Servers DDNS Service Yes, DVRLINK Included Remote Monitoring Immix, Monitorsoft Sentinel Interoperability ONVIF Profile S, HTTP/RTSP SDK Overstad Petrants WS-Discovery, RTP, RTSP, RTCP, SMTP, NTP, HTTP, FTP, Certifications Power Supply SMPS 51V/200W Max. 16W without HDD or cameras Fan 1 Dimensions 1U, (W) 380mm x (D) 314.6mm x (H) 44mm Rack Mount Supported Net Weight 2.75kg Operating Conditions 0°C to +40°C, 10%-90% Humidity (NC) Certifications CE FCC.	Remote Web Access			
PC Software P2P Cloud Service P2P Cloud Service PService Power Consumption Max. 16W without HDD or cameras Pan X1 Dimensions 1U, (W) 380mm x (D) 314.6mm x (H) 44mm PService P	Mobile App			
P2P Cloud Service Yes, European Servers DDNS Service Yes, DVRLINK Included Remote Monitoring Immix, Monitorsoft Sentinel Interoperability ONVIF Profile S, HTTP/RTSP SDK Overated Partners WS-Discovery, RTP, RTSP, RTCP, SMTP, NTP, HTTP, FTP, Certifications Fan				
DDNS Service Yes, DVRLINK Included Remote Monitoring Immix, Monitorsoft Sentinel Interoperability ONVIF Profile S, HTTP/RTSP SDK Overseted Retails WS-Discovery, RTP, RTSP, RTCP, SMTP, NTP, HTTP, FTP, Certifications DDMS 10, (W) 380mm x (D) 314.6mm x (H) 44mm Rack Mount Supported Net Weight 2.75kg Operating Conditions 0°C to +40°C, 10%-90% Humidity (NC) Certifications CERCC				
Remote Monitoring Immix, Monitorsoft Sentinel Net Weight Supported Interoperability ONVIF Profile S, HTTP/RTSP SDK Operating Conditions 0°C to +40°C, 10%-90% Humidity (NC) Overseted Parksola WS-Discovery, RTP, RTSP, RTCP, SMTP, NTP, HTTP, FTP, Overseted Parksola Sentine Supported Supp				
Interoperability ONVIF Profile S, HTTP/RTSP SDK Operating Conditions O°C to +40°C, 10%-90% Humidity (NC) Operating Conditions O°C to +40°C, 10%-90% Humidity (NC) Certifications Certifications		·		
WS-Discovery, RTP, RTSP, RTCP, SMTP, NTP, HTTP, FTP, Certifications CF FCC Certifications				
Supported Protocols WS-DISCOVERY, NTP, NTOP, NTO	ппеторегаршку			
THING THE PURINE BOTTLE POT FOR SOME THE STATE OF THE STA	Supported Protocols	Wo-DISCOVERY, RTP, RTOP, RTCP, SMIP, NTP, HTTP, FTP,	Certifications	CE, FCC
Dario, Drior, artific froduct of or of waving, Thirro, 33L		DDNO, DHOF, GENE (NOGLEI FOIL FOIWAGING), HTTPS, 55L		



DIMENSIONS



REAR PANEL



ORDER CODES

VUHDIPL-8-2/1000 Concept Pro Lite 8 Channel 8MP NVR 1TB VUHDIPL-8-2/2000 Concept Pro Lite 8 Channel 8MP NVR 2TB VUHDIPL-8-2/3000 Concept Pro Lite 8 Channel 8MP NVR 3TB VUHDIPL-8-2/4000 Concept Pro Lite 8 Channel 8MP NVR 4TB VUHDIPL-8-2/6000 Concept Pro Lite 8 Channel 8MP NVR 6TB VUHDIPL-8-2/8000 Concept Pro Lite 8 Channel 8MP NVR 8TB VUHDIPL-8-2/10000 Concept Pro Lite 8 Channel 8MP NVR 10TB VUHDIPL-8-2/12000 Concept Pro Lite 8 Channel 8MP NVR 12TB VUHDIPL-8-2/16000 Concept Pro Lite 8 Channel 8MP NVR 16TB VUHDIPL-8-2/20000 Concept Pro Lite 8 Channel 8MP NVR 20TB

