

Concept 🚫 Pro

5MP





AIR3525DEEL-IP5M-Z

Concept Pro 5MP IP Enhanced Low Light Motorised External Small Bullet Camera

The AIR3525DEEL-IP5M-Z model is an IP camera that has been designed to deliver the highest image quality for demanding external environments. This weather-resistant external small bullet features a 2.8-8mm motorised, smart infrared LEDs with 30m illumination range, and provides crisp 5-megapixel video. This camera is also designed for excellent compatibility with the Concept Pro range of network video recorders.



Deep Learning Motion Detection

Reduce false motion detection alarms by up to 95% using new Deep Learning Motion Detection technology. Trained with deep learning algorithms, the camera can recognise and trigger motion detection events only if a person is detected in the specified area. As a result, false alarms from sources such as lights, animals, foliage, weather, and other objects are effectively filtered and reduced.



Intelligent, Efficient Bit Rate Control

Reduce camera streaming bit rates by up to 90% by using Variable Bit Rate (VBR) or VBR+ smart bit rate control settings. These dynamic features maximise overall image quality while minimising camera stream bit rates. This results in lower network bandwidth usage and extended recording storage retention time.



Enhanced Low Light Performance

This model utilises an Enhanced Low Light CMOS sensor with greater light sensitivity, resulting in the camera capturing colour images long after standard CCTV cameras have switched to black & white night mode and brighter images in darker conditions.

KEY FEATURES

- Max. 25FPS @ 5MP
- 2.8-8mm Motorised Lens
- Up to 30m Smart IR Illumination

30M

IR

- Deep Learning Motion Detection
- H.265 Video Codec & VBR+ Smart Bit Rate Control
- Enhanced Low Light Performance

OTHER FEATURES

- PoE/DC12V Power Input
- True WDR, ATW, BLC, Defog, 3D-DNR
- Manual Regions of Interest
- ONVIF Profile S Compliant
- IP66-rated



AIR3525DEEL-IP5M-Z

Concept Pro 5MP IP Enhanced Low Light Motorised External Small Bullet Camera


SPECIFICATION


Model/Fea	atura	AIR3525DEEL-IP5M-Z
wouldrea	Video Output Type	
	Image Sensor	1/2.8" Progressive Scan CMOS
	Signal System	PAL/NTSC
	Min. Illumination	Enhanced Low Light Performance -
		Colour: 0.004 Lux @ (F2.0, AGC ON) B&W: 0 lux with IR LEDs on
•	Electronic Shutter	Auto/Manual, 1/25 to 1/5,000s
Camera	S/N Ratio	≥48dB
	IR LEDs	x4
	IR Illumination Range	Max. 30m
	IR Control	Auto/Off
	Adaptable IR	Auto
	Pan/Tilt/Rotation Range	P: 0°–360°, T: 0°–90°, R: 0°–360°
	Lens Type	Motorised Lens
	Mount Type	Built-in
	Focal Length	f=2.8-8mm
Lens	Aperture	F1.6
	Angle of View	H: 102.8-50.0°, V: 74.1-37.4°, D: 142.5-62.5°
	Focus	Auto/Manual Focus
	Iris	Fixed Iris
	Compression	H.265/H.264 with VBR+ Smart Codec Option
	Streaming Capability	Triple Streaming + SVC Stream
	Resolution	2592x1944, 2592x1520, 2304x1296, 2048x1536, 1920x1080,
		1280x1024, 1024x768, 1280x720, 704x576, 704x480, 640x480,
	France Data	640x360, 352x288, 352x240
	Frame Rate	Stream 1: Max. 25FPS @ 2592x1944
		Stream 2: Max. 25FPS @ 640x480 Stream 3: Max. 25FPS @ 640x480
	Bit Rate Control	CBR/VBR/VBR+
	Bit Rate	Stream 1: 1,000-8,000kbps
	Dil hale	Stream 2: 600-2,000kbps
		Stream 3: 600-2,000kbps
	Day/Night	True D&N with ICR (Auto/Day/Night/Schedule)
	Backlight Compensation	Yes
Video	Wide Dynamic Range	True WDR
VIGEO	White Balance	ATW/Manual (Indoor/Fluorescent/Outdoor)
	Gain Control	Auto
	Noise Reduction	3D-DNR (Auto/Manual)
	Region of Interest	Manual (Max. 8 Regions)
	Defog	Yes
	Slow Shutter	Off/X2/X4/X8
	Image Setting	Mirror/Flip
	Image Adjustment	Brightness, Contrast, Colour, Sharpness
	Privacy Masking	Yes (Max. 4 Areas)
	Motion Detection	Yes (Max. 4 Areas)
	Tamper Detection	Yes
	Deep Learning Motion Detection	Yes (Human Detection)
	Deep Learning Video Analytics	-
	Transmission Distance	Max. 100m over Ethernet
Network	Ethernet	x1 RJ45 10M/100M Ethernet
	Protocol	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS,
		DDNS, NTP, SMTP, FTP, UPnP, HTTP, HTTPS, SSL/TLS
	Interoperability	ONVIF Profile S, HTTP/RTSP API
	ONVIF Channels	Max. 4 Streams
	Streaming Method	Unicast/Multicast
	Max. User Access	x10
	Edge Storage	Local PC (Snapshot/Recording)
Interface	Video Interface	- ·
	Alarm Interface	-
	Audio Interface	-
	Audio Compression	N/A
	RS-485	- N1/A
	Control Protocol Reset Button	N/A Yes
General		
	Power Supply Power Consumption	PoE 802.3af (Class 0)/DC12V PoE: Max. 9.3W with IR on
	Power Consumption Power Output	FUE, IVIAX, 9.3VV WITH IN ON
	Operating Temperature	-20°C to +50°C
	Operating Humidity	
	Ingress Protection	0% 10 90%
	Vandal Resistance	IP00
	Housing Materials	- Aluminum Diecasting
	RAL	RAL7021 Black Grey
	Dimensions	(Ø) 66mm × (L) 209mm without sunshield
	Net Weight	(Ø) 66mm × (L) 209mm without sunshield ≈550g
	Gross Weight	≈330g ≈700g
Certification	Certifications	CE
Seranoauon	55. (IIIO00010	JL


Concept 🚫 Pro

DIMENSIONS

All measurements are in mm.







ORDER CODE

AIR3525DEEL-IP5M-Z

Concept Pro 5MP IP Enhanced Low Light Motorised External Small Bullet Camera

OTHER PRODUCTS IN THE RANGE

• AIR3525DEEL-IP5M/2.8

AIR3525DLEL-IP8M/2.8

Concept Pro 5MP IP Enhanced Low Light Fixed External Small Bullet Camera Concept Pro 8MP IP Deep Learning Fixed External Small Bullet Camera

Concept Pro Small Pendant Mount - Black Grey

Concept Pro Pole Mount

CAT6 Cable (Green)

Concept Pro Corner Mount

RECOMMENDED ACCESSORIES

+ CP-BASE-1-V2-G	Concept Pro Small Junction Box - Black Grey
 CP-WM-1-V2-G 	Concept Pro Small Wall Mount - Black Grey

- + CP-PM-1-V2-G
- CP-PLM-V2
- + CP-CM-V2
 - CAT6-305 305m
 - VA-SW4/8/16POE-IP 4/8/16 Channel PoE Switch



AIR3525DEEL-IP5M-Z

Concept Pro 5MP IP Enhanced Low Light Motorised External Small Bullet Camera



