Concept Pro
















VUHDIP-4-3

Concept Pro 4 Channel 8MP NVR with PoE

The VUHDIP-4-3 model is a four channel network video recorder designed to satisfy professional surveillance requirements. It has four channels of PoE/PoE+built-in, supports the latest H.265 video compression codec for greater storage and bandwidth savings, and provides real-time recording performance at up to 8-megapixel resolutions across all channels. It has an expanded alarm input interface, and is compatible with Deep Learning Plus.



Professional Remote Monitoring

Provides 24 hour remote monitoring for clients and is available on all Concept Pro recorders with Alarm Receiving Stations using Immix Cloud and Sentinel platforms.



Deep Learning Video Analytics

This product supports the latest Deep Learning video analytics technology when compatible Concept Pro IP cameras are connected. Easily configure Deep Learning Motion Detection and advanced video analytics rules from the recorder user interface and begin reducing false alarms by up to 95% with the power of Deep Learning.



NDAA Compliant

This product uses the latest in chipset technology from Taiwan and is developed in South Korea without the use of restricted components.



Enhanced Security

This product supports a suite of security-related features, including automatic password expiration, encryption, and more settings designed to ensure authorised users are accessing the device.

KEY FEATURES

- 4 PoE/PoE+ IP Camera Inputs
- H.265 & H.264 Video Codec Support
- Real-time 8MP Recording for all Channels
- Max. 3840x2160 4K UHD Display Output
- Up to 10TB Internal Hard Disk Capacity
- Smart Storage Compression
- x1/x1 Audio I/O with HDMI Audio Output
- x4/x1 Alarm I/O
- Compatible with Concept Pro Deep Learning Video Analytics & Deep Learning Plus
- WD Purple Surveillance Hard Disks Preinstalled

OTHER FEATURES

- NDAA-compliant
- Remote Monitoring via Concept Pro Viewer Mobile App
- Supported by i-PIMS license-free VMS
- Timeline, Thumbnail, Event, and Deep Learning Search Modes
- Instant Playback
- Integrated Virtual Alarm Support
- Mouse and remote included
- Total 86W PoE Capacity
- Fanless Design



VUHDIP-4-3

Concept Pro 4 Channel 8MP NVR with PoE



SPECIFICATION


Video and Andia		Event	
Video and Audio	v4	Alarm Inputs	x4 (NVR) + x4 (IP Camera)
IP Video Inputs Video Signal	x4 PAL/NTSC	Alarm Outputs	x1 (NVR Relay) + x4 (IP Camera)
Max. Resolution/Frame Rate	Max. 25/30FPS @ 3840x2160 (8MP 4K UHD) per channel	·	Alarm Recording, Alarm Output, PTZ Preset, E-mail/Mobile
Video Compression Codec	H.265/H.264 (BP, MP, HP)	Alarm Event Triggers	Push/FTP Event Notification, Video/OSD Pop-up, Buzzer
Incoming Bandwidth	Max. 37Mbps	Basic Motion Detection	Supported (Depending on IP Camera Specification)
Bit Rate Control	CBR/VBR/VBR+	Deep Learning Motion	Supported (Select Concept Pro IP Camera Models)
Bit Rate per Channel	Stream 1: 1,000-8,000Kbps	Detection	
	Stream 2: 600-2,000Kbps	DL Motion Detection Objects	Human/Car/Bike
Power over Ethernet (PoE)	x4		Motion Recording, Alarm Output, PTZ Preset, E-mail/Mobile
Inputs PoE Standard	PoE 802.3af/802.3at	Motion Event Triggers	Push/FTP Event Notification, Buzzer
	Max. 25W per channel		Video Loss, Disk Overwrite Start, Disk Full, Disk Space x%
PoE Output	Max. 86W total	System Event Types	Exhausted, HDD SMART, No Disk, Panic Record Start, Booting,
PTZ Cameras	Supported, Network/RS485 (Pan/Tilt/Zoom, Scan, Tour,	System Event Types	Login Fail, PoE Fail, Trouble in Internet Connection, Fail in DDNS
	Preset Add/Delete/Sync)		Update, IP Conflict
Audio Inputs	x1 (RCA) + x4 (IP Camera Audio Input)	POS/ATM Events	Supported Concept Pro Deep Learning Plus & Deep Learning IP Cameras
Audio Outputs	x1 (RCA)/x1 (HDMI)	Deep Learning Events	Supported
Two-way Audio Audio Compression Codec	Supported G.711µ-law	Deep Learning Objects	Human/Car/Bike
Recording	G.7 T p-law		Forward/Reverse Line Crossing, Intrusion, Region Enter/Exit,
Recording Resolution	8MP (3840x2160)/5MP/4MP/3MP/2MP/1MP/D1/CIF	Deep Learning Rule Types	Loitering, Stopping, Counter
Recording Rate	Max. 100/120FPS @ 3840x2160 (8MP 4K UHD)	Deep Learning Live Timeline	Supported, with Object Thumbnails & Instant Playback
Recording Modes	Automatic/Manual Recording Profiles with	Deep Learning Event	DL/Alarm Recording, Alarm Out, Preset, Buzzer, Video Popup,
	Continuous, Motion, Deep Learning/Alarm, Panic Modes	Triggers Deep Learning Double	E-mail Notification, FTP Notification, Mobile App Push Message
Recording Scheduling	Hourly/Daily/Weekly	Nock	Supported
Pre-Event Recording	Yes, 0/1/2/3/4/5/10/15s	E-mail Notification	Yes, Snapshot Optional
Post-Event Recording Smart Storage Compression	Yes, 5/10/15/20/30/60/180s	E-mail Notification Schedule	Yes, Max. 10 Schedule Profiles
(SSC)	Supported	Alarm Arm/Disarm Function	Supported
Display		Storage	
Main Display Outputs	HDMI x1, VGA x1	Internal Hard Disk	SATA x1, Max. 10TB
Display Resolution	3840x2160/2560x1440/1920x1080/1280x124/1280x720	Hard Disk Health Monitoring	Yes (SMART)
Display Configuration	Auto/Manual	RAID Configuration	No, please see VUHDIPE model
Dual Monitor Functionality	Main Display Mirroring	Partial Data Deletion	Supported
Display Decoding Rate	Max. 100/120FPS; Max. 30FPS@8MP 1CH/4CH	Faitiai Data Deletion	Supported
Split Screen Mode Programmable Sequence	Supported, 1CH/4CH	External Storage Support	FTP (Backup)
Spot Monitor Output	BNC x1	Security	(
Spot Monitor Mode	Customisable, 1CH/4CH Split Screen Modes	Enhanced Security Rules	Supported, enabled by default
Search & Playback		Covert Channels	Supported, configurable by user and group authority
Search Modes	Calendar (Date/Time), Timeline, Thumbnail, Event, Text-in	Privacy Masking	Supported (Select Concept Pro IP Camera Models)
	(POS), Deep Learning	User Groups Number of Users	Admin/Manager/User Max. x10
Event Search Options	Alarm, Video, System, Network, Setup, Motion, Record, Storage, IPCAM, POS/ATM	Number of osers	Search, Archiving, System Setup, Record Setup, Event Action
Deep Learning Search	<u> </u>	Group Authority	Control, Listen to Audio, Microphone, Remote Login, PTZ
Options	Event Type, Object/Keyword		Control, Shutdown
Playback Decoding Rate	Max. 100/120FPS; Max. 30FPS@8MP		Unrequired network protocols off by default (SNMP, FTP, DDNS,
Split Screen Mode	1CH/4CH	Network Security	P2P, etc.), RTSP encryption (SEED_128), HTTPS Digest, IP filter,
Playback Speed	1x/2x/4x/8x/16x/32x/64x	-	Netstat, Ping test, IP conflict list, Live connected clients list with
Quick Playback	Yes, via Live Menu Timeline or Quick Menu		lockout, Auto Port Forwarding off by default
Archiving			Required ADMIN password change, password recovery e-mail
Archiving Devices	USB, FTP		authentication, enhanced user ID/password on by default, direct user ID input on by default, audio transmission and recording off
Remote Archiving	Web, i-PIMS (PC), FTP, Concept Pro Viewer Mobile App	System Security	by default, auto logout, password expiration, system log, user
Archived Video Format	RAW/AVI	-	authority, password check for search/backup, password check
Archive File Size Backup Encryption	Max. 20GB MD5 with Built-in Verification Watermark		for disk management, Encrypted System Settings File Import/
Snapshot	Live, Playback (JPEG)		Export
Bookmarking	Supported	Interface	
Reserved Data Management	Supported	USB	x2 (Front)
Network	· ·	RS-485	x1 (Pelco-D, Pelco-P, D-max, etc.)
Network Interface	x1 RJ45 10/100M Ethernet	Keyboard Controller	Supported (RS-485)
Max. User Connections	x10	Remote Control RS-232	Included
Transmission Rate	Max. 100/120FPS	System	
Adaptive Network Streaming	Supported		English, Spanish, German, French, Dutch, Italian, Korean,
Outgoing Bandwidth IP Address Support	Max. 72Mbps IPv4, IPv6	Language	Chinese, Japanese, Polish
Dual SMTP E-mail Server	Supported	Max. UTP Transmission	90m
	Internet Explorer: Live Video, Search, Playback, Setup	Firmware Upgrade	USB, Network
Remote Web Access	Chrome, Firefox: Live JPEG, Setup	Operating System	Concept Pro User Interface, NDAA-compliant SoC
Mobile App	Concept Pro Viewer (iOS/Android)	General Power Supply	DC48V/2A Power Adapter
PC Software	i-PIMS CMS	Power Consumption	Max. 6W without HDD or cameras
P2P Cloud Service	Yes, European Servers	Fan	-
DDNS Service	Yes, DVRLINK Included	Dimensions	Mini 1U, (W) 260mm x (D) 262.6mm x (H) 44mm
Remote Monitoring	Immix, Monitorsoft Sentinel	Rack Mount	-
Interoperability	ONVIF Profile S, HTTP/RTSP SDK	Net Weight	1/55kg
Supported Protocols	WS-Discovery, RTP, RTSP, RTCP, SMTP, NTP, HTTP, FTP, DDNS, DHCP, uPNP (Router Port Forwading), HTTPS, SSL	Operating Conditions	0°C to +40°C, 10%-90% Humidity (NC)
	_,, b (Hodds 1 o.t. o. waaiiig), 111 11 o, ool	-	

VUHDIP-4-3


Concept Pro 4 Channel 8MP NVR with PoE



DIMENSIONS



REAR PANEL



ORDER CODES

VUHDIP-4-3/1000	Concept Pro 4 Channel 8MP NVR 1TB
VUHDIP-4-3/2000	Concept Pro 4 Channel 8MP NVR 2TB
VUHDIP-4-3/3000	Concept Pro 4 Channel 8MP NVR 3TB
VUHDIP-4-3/4000	Concept Pro 4 Channel 8MP NVR 4TB
VUHDIP-4-3/6000	Concept Pro 4 Channel 8MP NVR 6TB
VUHDIP-4-3/8000	Concept Pro 4 Channel 8MP NVR 8TB
VUHDIP-4-3/10000	Concept Pro 4 Channel 8MP NVR 10TB

