



2MP

4mm Fixed Lens 30M IR

4 in 1 Analogue

# AIR3525EL-AHD2M/4

# Concept Pro Lite 2MP AHD Enhanced Low Light Fixed External Small Bullet Camera (4mm)

The AIR3525EL-AHD2M/4 model is a 4-in-1 analogue camera that has been designed to deliver the highest image quality for demanding external environments. This weather-resistant external small bullet features a 4mm fixed lens, smart infrared LEDs with 30m illumination range, and provides crisp 2-megapixel video at real-time frame rates with true wide dynamic range and enhanced low light performance. This camera is also designed for excellent compatibility with the Concept Pro range of hybrid digital video recorders.



#### **True Wide Dynamic Range**

With true wide dynamic range, this camera can capture sharp images throughout the entire field of view, even when there are severe differences between light levels.



# **Enhanced Low Light Performance**

This CCTV camera utilises an Enhanced Low Light CMOS sensor with greater light sensitivity, resulting in the camera capturing colour images long after standard CCTV cameras have switched to black and white night mode.



#### Four-in-one solution

Don't be tied down to any single analogue platform. With Concept Pro 4-in-1 cameras you have the freedom to install whichever CCTV platform you like, whether you install AHD, TVI, CVI, or traditional analogue systems.

# **KEY FEATURES**

- Max. 25FPS @ 2MP
- 4mm Fixed Lens
- Up to 30m Smart IR Illumination
- 4-in-1 Operation (AHD/TVI/CVI/CVBS)
- Enhanced Low Light Performance
- True Wide Dynamic Range

# **OTHER FEATURES**

- DC12V Power Input
- Up the Coax Coaxitron Support
- AGC, Sens-up, AWB, BLC, HLC, Defog
- IP66-rated

# ANALOGUE HD TYPICAL CABLE DISTANCE



**DVR** 

	5MP	2MP	720P
COAX (RG59)	UP TO 500M	UP TO 500M	UP TO 500M
CAT5e	UP TO 200M	UP TO 305M	UP TO 350M
CAT6	UP TO 200M	UP TO 305M	UP TO 350M

\*Approximate distances calculated using HD MasterBaluns. Actual transmission range will vary depending on type and quality of cable and baluns.



# AIR3525EL-AHD2M/4




Concept Pro Lite 2MP AHD Enhanced Low Light Fixed External Small Bullet Camera (4mm)


# **SPECIFICATION**


Model/Featu	ure	AIR3525EL-AHD2M/4	
	Image Sensor	1/2.8" Progressive Scan CMOS	
	Video Output Type	AHD/TVI/CVI/CVBS	
	Signal System	PAL/NTSC	
	Min. Illumination	Colour: 0.02 lux (Enhanced Low Light) B&W: 0.002 lux (Enhanced Low Light) 0 lux with IR on	
Camera	Electronic Shutter	Auto/Manual, 1/25-1/25,600s	
	S/N Ratio	≥50dB	
	IR LEDs	x4	
	IR Illumination Range	Max. 30m	
	IR Control	On/Off	
	Adaptable IR	Auto	
	Pivot Axis	Pan: 0-360°, Tilt: 0-75°, Rotation: 0-360°	
	Lens Type	Fixed	
Lens	Mount Type	Built-in	
	Focal Length	f=4mm	
	Aperture	F2.0	
	Angle of View	H:82°, V:44°, D:99°	
	Focus	Fixed	
	Iris	Fixed	
	Resolution		
	1 IOSOIUIIOI I	2MP (1920 x 1080), SD (960 x 576)  AHD/TVI/CVI: 25/30FPS @ 2MP	
	Frame Rate	CVBS: 25/30FPS @ SD	
	Day/Night	True Day & Night with ICR (Auto/Colour/B&W/EXT)	
	Backlight Compensation	BLC/HLC	
	Wide Dynamic Range	True WDR	
	White Balance	Auto/AutoExt/Preset/Manual	
	Gain Control	Auto (AGC, 0–20)	
/ideo	Noise Reduction	2D/3D-DNR (High/Middle/Low/Off)	
	Motion Detection	Yes	
	Defog	-	
	Image Setting	Freeze, Flip	
	Image Adjustment	Brightness, Sharpness, Colour Gain, Ace, Gamma	
	Privacy Masking	Yes	
	Sens-Up	Yes (x2/x4/x8/x16/x32/Off)	
		· · · · · · · · · · · · · · · · · · ·	
	Transmission Distance	Max. 500m (1Vp-p 75Ω)	
	Video Output Audio Interface	x1 1.0Vp-p 75Ω BNC (AHD/TVI/CVI/CVBS)	
nterface	RS-485	- N/A	
	Control Protocol	N/A	
	Up the Coax (Coaxitron) Support	Yes	
	OSD Buttons	Yes PO10V-100V	
	Power Supply	DC12V±10%	
	Power Output	- May OM	
	Power Consumption	Max. 6W	
General	Operating Temperature	-30°C to +50°C	
	Operating Humidity	20–80% RH	
	Ingress Protection	IP66	
	Impact Resistance	<u>-</u>	
	Housing Materials	Aluminum Diecasting	
	RAL	RAL 7021 Black Grey	
	Dimension	(Ø) 66mm × (L) 209mm without sunshield	
	Net Weight	≈350g	
	Gross Weight	≈550g	
Certification	Certifications	CE	

#### **DIMENSIONS**

#### All measurements are in mm.







## ORDER CODE

• AIR3525EL-AHD2M/4

Concept Pro Lite 2MP AHD Enhanced Low Light Fixed External Small Bullet Camera (4mm)

#### OTHER PRODUCTS IN THE RANGE

• AIR3525EL-AHD2M/2.8

Concept Pro Lite 2MP AHD Enhanced Low Light Fixed External Small Bullet Camera

AIR3525EL-AHD5M/2.8

Concept Pro 5MP AHD Enhanced Low Light Fixed External Small Bullet Camera

• AIR3525EL-AHD5M/4

Concept Pro 5MP AHD Enhanced Low Light Fixed External Small Bullet Camera (4mm)

# RECOMMENDED ACCESSORIES

• CP-BASE-1-V2-G • CP-WM-1-V2-G Concept Pro Small Junction Box - Black Grey Concept Pro Small Wall Mount - Black Grey

• CP-PM-1-V2-G • CP-PLM-V2 Concept Pro Small Pendant Mount - Black Grey Concept Pro Pole Mount

• CP-CM-V2

Concept Pro Corner Mount RG59 Coaxial Cable 100m (Black))

• RG59K-100 • RG59K-500

RG59 Coaxial Cable 500m (Black)

COMPATIBLE WITH



# AIR3525EL-AHD2M/4




Concept Pro Lite 2MP AHD Enhanced Low Light Fixed External Small Bullet Camera (4mm)

ACCESSORIES DIMENSIONS

## CP-BASE-1-V2-G

Concept Pro Small Junction Box






# CP-PM-1-V2-G

Concept Pro Small Pendant Mount






# CP-WM-1-V2-G

Concept Pro Small Wall Mount






# CP-PLM-V2

Concept Pro Pole Mount (can be combined with CP-BASE-1-V2)





# CP-CM-V2

Concept Pro Corner Mount (can be combined with CP-BASE-1-V2)



