



2MP

2.8mm Fixed Lens 20M IR

4 in 1

CVP5325IREL-AHD2M/2.8

Concept Pro Lite 2MP AHD Fixed External Compact Vandal Dome Camera

The CVP5325IREL-AHD2M/2.8 model is a 4-in-1 analogue camera that has been designed to deliver the highest image quality for demanding external environments. This weather-resistant compact external dome features a 2.8mm fixed lens, smart infrared LEDs with 20m illumination range, and provides crisp 2-megapixel video at real-time frame rates with true wide dynamic range and enhanced low light performance. This camera is also designed for excellent compatibility with the Concept Pro range of hybrid digital video recorders.



True Wide Dynamic Range

With true wide dynamic range, this camera can capture sharp images throughout the entire field of view, even when there are severe differences between light levels.



Enhanced Low Light

This CCTV camera utilises an Enhanced Low Light CMOS sensor with greater light sensitivity, resulting in the camera capturing colour images long after standard CCTV cameras have switched to black & white night mode.



DC12V Power Output

This CCTV camera also provides a DC12V 100mA power output that can be conveniently used to power some auxiliary equipment rather than using a separate power supply adapter.

KEY FEATURES

- Max. 25FPS @ 2MP
- 2.8mm Fixed Lens
- Up to 20m Smart IR Illumination
- 4-in-1 Operation (AHD/TVI/CVI/CVBS)
- Enhanced Low Light Performance
- True Wide Dynamic Range

OTHER FEATURES

- DC12V/AC24V Power Input
 & DC12V Power Output
- Up the Coax Coaxitron Support
- AGC, Sens-up, AWB, BLC, HLC, Defog
- IP66 & IK10-rated
- Smoked Dome Bubble Options Available

ANALOGUE HD TYPICAL CABLE DISTANCE



DVR

	5MP	2MP	720P
COAX (RG59)	UP TO 500M	UP TO 500M	UP TO 500M
CAT5e	UP TO 200M	UP TO 305M	UP TO 350M
CAT6	UP TO 200M	UP TO 305M	UP TO 350M

*Approximate distances calculated using HD MasterBaluns. Actual transmission range will vary depending on type and quality of cable and baluns.



CVP5325IREL-AHD2M/2.8

Concept Pro Lite 2MP AHD Fixed External Compact Vandal Dome Camera



SPECIFICATION


ge Sensor O Output Type al System Illumination tronic Shutter Ratio EDS urnination Range ontrol otable IR t Axis § Type	1/2.8" Progressive Scan CMOS AHD/TV/CVI/CVBS PAL/NTSC Colour: 0.002 lux (Enhanced Low Light) B&W: 0.0002 lux (Enhanced Low Light) 0 lux with IR on Auto/Manual, 1/25–1/25,600s ≥50dB x4 Max. 20m On/Off Auto	
al System Illumination tronic Shutter Ratio EDs umination Range ontrol otable IR t Axis	PAL/NTSC Colour: 0.002 lux (Enhanced Low Light) B&W: 0.0002 lux (Enhanced Low Light) 0 lux with IR on Auto/Manual, 1/25-1/25,600s ≥50dB x4 Max.20m On/Off	
Illumination tronic Shutter Ratio EDs urnination Range ontrol otable IR t Axis	Colour: 0.002 lux (Enhanced Low Light) B&W: 0.0002 lux (Enhanced Low Light) 0 lux with IR on Auto/Manual, 1/25-1/25,600s ≥50dB x4 Max. 20m On/Off	
tronic Shutter Ratio EDs umination Range ontrol otable IR t Axis	B&W: 0.0002 lux (Enhanced Low Light) 0 lux with IR on Auto/Manual, 1/25–1/25,600s ≥50dB x4 Max. 20m On/Off	
Ratio EDs umination Range ontrol otable IR t Axis	Auto/Manual, 1/25–1/25,600s ≥50dB ×4 Max. 20m On/Off	
Ratio EDs umination Range ontrol otable IR t Axis	≥50dB x4 Max. 20m On/Off	
EDs umination Range ontrol otable IR t Axis	x4 Max. 20m On/Off	
umination Range ontrol otable IR t Axis	Max. 20m On/Off	
ontrol otable IR t Axis	On/Off	
otable IR t Axis	1 1 1	
t Axis	Auto	
Type	Pan: 0-353°, Tilt: 0-70°, Rotation: 0-176°	
	Fixed	
nt Type	Built-in	
al Length	f=2.8mm	
rture	F2.0	
e of View	H: 104°, V: 76°, D: 112°	
JS	Fixed	
	Fixed	
olution	2MP (1920 x 1080), SD (960 x 576)	
ne Rate	AHD/TVI/CVI: 25/30FPS @ 2MP CVBS: 25/30FPS @ SD	
/Night	True Day & Night with ICR (Auto/Colour/B&W/EXT)	
klight Compensation	BLC/HLC	
e Dynamic Range	True WDR	
e Balance	Auto/AutoExt/Preset/Manual	
Control	Auto (AGC, 0-20)	
e Reduction	2D/3D-DNR (High/Middle/Low/Off)	
on Detection	Yes	
pq	Yes	
ge Setting	Freeze, Flip	
ge Adjustment	Brightness, Sharpness, Colour Gain, Ace, Gamma	
acy Masking	Yes	
s-Up	Yes (x2/x4/x8/x16/x32/Off)	
smission Distance	Max. 500m (1Vp-p 75Ω)	
o Output	x1 1.0Vp-p 75Ω BNC (AHD/TVI/CVI/CVBS) x1 2-pin UTP Video Output	
io Interface	-	
485	-	
trol Protocol	N/A	
he Coax (Coaxitron) Support	Yes	
Buttons	Yes	
ver Supply	DC12V±10%/AC24V±10%	
er Output	DC12V. Max. 100mA	
er Consumption	Max. 6.5W	
rating Temperature	-30°C to +40°C	
rating Humidity	20-80% RH	
	IP66	
act Resistance	IK10	
	Aluminum Diecasting	
	RAL 9010 Pure White	
	Ø110.8×81.8mm	
	≈450q	
	≈430g ≈650g	
se Woight	≈ooug CE	
es si er W	s Protection	


RECOMMENDED ACCESSORIES


+ CP-BASE-1-V2 Concept Pro Small Junction Box CP-WM-1-V2 Concept Pro Small Wall Mount Concept Pro Small Pendant Mount CP-TM-1-V2 Concept Pro Small In-ceiling/Tile Mount • CP-PLM-V2 Concept Pro Pole Mount + CP-CM-V2 Concept Pro Corner Mount CP-RC-V2 Concept Pro Rain Cap • RG59K-100 RG59 Coaxial Cable 100m (Black) RG59K-500 RG59 Coaxial Cable 500m (Black)

DIMENSIONS

All measurements are in mm.







ORDER CODE

• CVP5325IREL-AHD2M/2.8

Concept Pro Lite 2MP AHD Fixed External Compact Vandal Dome Camera

OTHER PRODUCTS IN THE RANGE

CVP5325IREL-AHD2M/4
Concept Pro Lite 2MP AHD Fixed External Compact Vandal Dome Camera (4mm)

CVP5325IREL-AHD5M/2.8 Concept Pro 5MP AHD Fixed External Compact Vandal Dome Camera

CVP5325IREL-AHD2M/WA Concept Pro Lite 2MP AHD Wide Angle Fixed External Compact Vandal

Dome Camera

CVP5325IREL-AHD5M/WA

Concept Pro Lite 5MP AHD Wide
Angle Fixed External Compact Vandal

Dome Camera

CVP5325IREL-AHD2M/2.8-SD Concept Pro Lite 2MP AHD Smoked

Dome Fixed External Compact Vandal Dome Camera

CVP5325IREL-AHD2M/4-SD Concept Pro Lite 2MP AHD Smoked

Dome Fixed External Compact Vandal Dome Camera (4mm)

CVP5325IREL-AHD5M/2.8-SD Concept Pro 5MP AHD Smoked Dome Fixed External Compact Vandal Dome Camera

CVP5325IREL-AHD2M/WA-SD Concept Pro Lite 2MP AHD Smoked Dome Wide Angle Fixed External Compact Vandal Dome Camera

CVP5325IREL-AHD5M/WA-SD Concept Pro 5MP AHD Smoked Dome Wide Angle Fixed External Compact Vandal Dome Camera

CVP5325IREL-AHD2M/2.8

Concept Pro Lite 2MP AHD Fixed External Compact Vandal Dome Camera




ACCESSORIES

CP-TM-1-V2

Concept Pro Small In-ceiling/Tile Mount



DIMENSIONS







CP-BASE-1-V2

Concept Pro Small Junction Box












Concept Pro Small Pendant Mount






CP-WM-1-V2

Concept Pro Small Wall Mount





CP-PLM-V2

Concept Pro Pole Mount (can be combined with CP-BASE-2-V2)








CP-CM-V2

Concept Pro Corner Mount (can be combined with CP-BASE-2-V2)







CP-RC-V2