



2MP

3mm Fixed Lens 20M IR

4 in 1

CVP5325IREL-AHD2M/WA

Concept Pro Lite 2MP AHD Wide Angle Fixed External Compact Vandal Dome Camera

The CVP5325IREL-AHD2M/WA model is a 4-in-1 analogue camera that has been designed to deliver the highest image quality for demanding external environments. This weather-resistant compact external dome features a 3mm fixed lens, smart infrared LEDs with 20m illumination range, and provides crisp 2-megapixel video at real-time frame rates with true wide dynamic range and enhanced low light performance. This camera is also designed for excellent compatibility with the Concept Pro range of hybrid digital video recorders.



True Wide Dynamic Range

With true wide dynamic range, this camera can capture sharp images throughout the entire field of view, even when there are severe differences between light levels.



Enhanced Low Light

This CCTV camera utilises an Enhanced Low Light CMOS sensor with greater light sensitivity, resulting in the camera capturing colour images long after standard CCTV cameras have switched to black & white night mode.



DC12V Power Output

This CCTV camera also provides a DC12V 100mA power output that can be conveniently used to power some auxiliary equipment rather than using a separate power supply adapter.

KEY FEATURES

- Max. 25FPS @ 2MP
- 3mm Fixed Lens
- Up to 20m Smart IR Illumination
- 4-in-1 Operation (AHD/TVI/CVI/CVBS)
- Enhanced Low Light Performance
- True Wide Dynamic Range

OTHER FEATURES

- DC12V/AC24V Power Input
 & DC12V Power Output
- Up the Coax Coaxitron Support
- AGC, Sens-up, AWB, BLC, HLC, Defog
- IP66 & IK10-rated

ANALOGUE HD TYPICAL CABLE DISTANCE



DVR

	5MP	2MP	720P
COAX (RG59)	UP TO 500M	UP TO 500M	UP TO 500M
CAT5e	UP TO 200M	UP TO 305M	UP TO 350M
CAT6	UP TO 200M	UP TO 305M	UP TO 350M

*Approximate distances calculated using HD MasterBaluns. Actual transmission range will vary depending on type and quality of cable and baluns.



CVP5325IREL-AHD2M/WA

Concept Pro Lite 2MP AHD Wide Angle Fixed External Compact Vandal Dome Camera



SPECIFICATION


Model/Fe	eature	CVP5325IREL-AHD2M/WA	
	Image Sensor	1/2.8" Progressive Scan CMOS	
	Video Output Type	AHD/TVI/CVI/CVBS	
	Signal System	PAL/NTSC	
	Min. Illumination	Colour: 0.002 lux (Enhanced Low Light)	
		B&W: 0.0002 lux (Enhanced Low Light) 0 lux with IR on	
Camera	Electronic Shutter	Auto/Manual, 1/25-1/25,600s	
	S/N Ratio	≥50dB	
	IR LEDs	x4	
	IR Illumination Range	Max. 20m	
	IR Control	On/Off	
	Adaptable IR	Auto	
	Pivot Axis	Pan: 0-353°, Tilt: 0-70°, Rotation: 0-176°	
Lens	Lens Type	Fixed	
	Mount Type	Built-in	
	Focal Length	f=3mm	
	Aperture	F2.0	
	Angle of View	H:120°, V:65°,D:146°	
	Focus	Fixed	
	Iris	Fixed	
	Resolution	2MP (1920 x 1080), SD (960 x 576)	
	Frame Rate	AHD/TVI/CVI: 25/30FPS @ 2MP CVBS: 25/30FPS @ SD	
	Day/Night	True Day & Night with ICR (Auto/Colour/B&W/EXT)	
	Backlight Compensation	BLC/HLC	
	Wide Dynamic Range	True WDR	
	White Balance	Auto/AutoExt/Preset/Manual	
Video	Gain Control	Auto (AGC, 0–20)	
	Noise Reduction	2D/3D-DNR (High/Middle/Low/Off)	
	Motion Detection	Yes	
	Defog	Yes	
	Image Setting	Freeze, Flip	
	Image Adjustment	Brightness, Sharpness, Colour Gain, Ace, Gamma	
	Privacy Masking	Yes	
	Sens-Up	Yes (x2/x4/x8/x16/x32/Off)	
	Transmission Distance	Max. 500m (1Vp-p 75Ω)	
Interface	Video Output	x1 1.0Vp-p 75Ω BNC (AHD/TVI/CVI/CVBS) x1 2-pin UTP Video Outpu	
	Audio Interface	-	
	RS-485		
	Control Protocol	N/A	
	Up the Coax (Coaxitron) Support	Yes	
	OSD Buttons	Yes	
General	Power Supply	DC12V±10%/AC24V±10%	
	Power Output	DC12V±10%/AC24V±10% DC12V. Max. 100mA	
	Power Consumption	Max, 6,5W	
	Operating Temperature	-30°C to +40°C	
	Operating Humidity	20–80% RH	
	Ingress Protection	20-80% RH IP66	
	Impact Resistance	IK10	
	Housing Materials RAL	Aluminum Diecasting	
		RAL 9010 Pure White	
	Dimension	Ø110.8×81.8mm	
	Net Weight	≈450g	
	Gross Weight	≈650g	

RECOMMENDED ACCESSORIES

CP-BASE-1-V2 Concept Pro Small Junction Box
 CP-WM-1-V2 Concept Pro Small Wall Mount
 CP-PM-1-V2 Concept Pro Small Pendant Mount
 CP-TM-1-V2 Concept Pro Small In-ceiling/Tile Mount
 CP-PLM-V2 Concept Pro Pole Mount
 CP-CM-V2 Concept Pro Corner Mount
 CP-RC-V2 Concept Pro Rain Cap
 RG59K-100 RG59 Coaxial Cable 100m (Black)
 RG59K-500 RG59 Coaxial Cable 500m (Black)

DIMENSIONS

All measurements are in mm.



ORDER CODE

CVP5325IREL-AHD2M/WA

Concept Pro Lite 2MP AHD Wide Angle Fixed External Compact Vandal Dome Camera

OTHER PRODUCTS IN THE RANGE

CVP5325IREL-AHD2M/2.8 Concept Pro Lite 2MP AHD Fixed External Compact Vandal Dome

Camera

CVP5325IREL-AHD5M/2.8 Concept Pro 5MP AHD Fixed External

Compact Vandal Dome Camera

CVP5325IREL-AHD2M/4 Concept Pro Lite 2MP AHD Fixed

External Compact Vandal Dome Camera (4mm)

CVP5325IREL-AHD5M/4 Concept Pro 5MP AHD Fixed External

Compact Vandal Dome Camera (4mm)

CVP5325IREL-AHD5M/WA Concept Pro 5MP AHD Wide Angle

Fixed External Compact Vandal Dome

CVP5325IREL-AHD2M/2.8-SD Concept Pro 2MP AHD Smoked Dome Fixed External Compact Vandal

Dome Camera

CVP5325IREL-AHD5M/2.8-SD Concept Pro 5MP AHD Smoked

Dome Fixed External Compact Vandal Dome Camera

CVP5325IREL-AHD2M/4-SD Concept Pro Lite 2MP AHD Smoked

Dome Fixed External Compact Vandal

Dome Camera (4mm)

CVP5325IREL-AHD5M/4-SD Concept Pro 5MP AHD Smoked Dome Fixed External Compact Vandal

Dome Camera (4mm)

CVP5325IREL-AHD2M/WA-SD Concept Pro Lite 2MP AHD Smoked Dome Wide Angle Fixed External

Compact Vandal Dome

CVP5325IREL-AHD5M/WA-SD Concept Pro 5MP AHD Smoked Dome Wide Angle Fixed External Compact Vandal Dome

CVP5325IREL-AHD2M/WA

Concept Pro Lite 2MP AHD Wide Angle Fixed External Compact Vandal Dome Camera




ACCESSORIES

CP-TM-1-V2

Concept Pro Small In-ceiling/Tile Mount



DIMENSIONS







CP-BASE-1-V2

Concept Pro Small Junction Box












CP-PM-1-V2

Concept Pro Small Pendant Mount





CP-WM-1-V2

Concept Pro Small Wall Mount













CP-PLM-V2

Concept Pro Pole Mount (can be combined with CP-BASE-2-V2)








CP-CM-V2

Concept Pro Corner Mount (can be combined with CP-BASE-2-V2)







CP-RC-V2