



5MP

2.8mm Fixed Lens 20M IR

4 in 1

CVP5325IREL-AHD5M/2.8

Concept Pro 5MP 4-in-1 Analogue Fixed Compact External Dome Camera

The CVP5325IREL-AHD5M/2.8 model is a 4-in-1 analogue camera that has been designed to deliver the highest image quality for demanding external environments. This weather-resistant compact external dome features a 2.8mm fixed lens, smart infrared LEDs with 20m illumination range, and provides crisp 5-megapixel video with true wide dynamic range and enhanced low light performance. This camera is also designed for excellent compatibility with the Concept Pro range of hybrid digital video recorders.



True Wide Dynamic Range

With true wide dynamic range, this camera can capture sharp images throughout the entire field of view, even when there are severe differences between light levels.



Enhanced Low Light

This CCTV camera utilises an Enhanced Low Light CMOS sensor with greater light sensitivity, resulting in the camera capturing colour images long after standard CCTV cameras have switched to black & white night mode.



DC12V Power Output

This CCTV camera also provides a DC12V 100mA power output that can be conveniently used to power some auxiliary equipment rather than using a separate power supply adapter.

KEY FEATURES

- Max. 20FPS @ 5MP
- 2.8mm Fixed Lens
- Up to 20m Smart IR Illumination
- 4-in-1 Operation (AHD/TVI/CVI/CVBS)
- Enhanced Low Light Performance
- True Wide Dynamic Range

OTHER FEATURES

- DC12V/AC24V Power Input
 & DC12V Power Output
- Up the Coax Coaxitron Support
- AGC, 3D-DNR, BLC
- IP66-rated
- Smoked Dome Bubble Options Available

ANALOGUE HD TYPICAL CABLE DISTANCE



DVR

	5MP	2MP	720P
COAX (RG59)	UP TO 500M	UP TO 500M	UP TO 500M
CAT5e	UP TO 200M	UP TO 305M	UP TO 350M
CAT6	UP TO 200M	UP TO 305M	UP TO 350M

*Approximate distances calculated using HD MasterBaluns. Actual transmission range will vary depending on type and quality of cable and baluns.



CVP5325IREL-AHD5M/2.8

Concept Pro 5MP 4-in-1 AHD Fixed Lens Compact Vandal Dome Camera



SPECIFICATION

Model/Fe	eature	CVP5325IREL-AHD5M/2.8	
	Image Sensor	1/2.8" Progressive Scan CMOS	
	Video Output Type	AHD/TVI/CVI/CVBS	
	Signal System	PAL/NTSC	
	Min. Illumination	Colour: 0.4 lux (Enhanced Low Light)	
		B&W: 0.04 lux (Enhanced Low Light) 0 lux with IR on	
0	Electronic Shutter	Auto	
Camera	S/N Ratio	≥50dB	
	IR LEDs	x4	
	IR Illumination Range	Max. 20m	
	IR Control	On/Off	
	Adaptable IR	Auto	
	Pivot Axis	Pan: 0-353°, Tilt: 0-70°, Rotation: 0-176°	
Lens	Lens Type	Fixed	
	Mount Type	Built-in	
	Focal Length	f=2.8mm	
	Aperture	F2.0	
	Angle of View	H: 104°, V: 76°, D: 112°	
	Focus	Fixed	
	Iris	Fixed	
	Resolution	5MP (2592x1944), 4MP (2560x1440), 2MP (1920 x 1080), SD (960 x 5	
	Frame Rate	AHD/TVI: 12.5/20FPS @ 5MP, 15/25/30FPS @ 4MP, 25/30FPS @ 2M	
	Traine hate	CVI: 25/30FPS @ 4MP, 25/30FPS @ 2MP	
		CVBS: 25/30FPS @ SD	
	Day/Night	True Day & Night with ICR (Auto/Colour/B&W/EXT)	
	Backlight Compensation	BLC/Global	
Video	Wide Dynamic Range	True WDR	
	White Balance	Pro/Gray World	
	Gain Control	Auto	
	Noise Reduction	3D-DNR (Auto/Manual)	
	Motion Detection	OD DINIT (Auto/Manda)	
	Defog		
	Image Setting	Mirror	
	Image Adjustment	Brightness, Sharpness, Contrast, Saturation	
	Privacy Masking	Brightness, Sharphess, Contrast, Saturation	
	Sens-Up	•	
		May 500m (1) (n n 750)	
	Transmission Distance	Max. 500m (1Vp-p 75Ω)	
	Video Output	x1 1.0Vp-p 75Ω BNC (AHD/TVI/CVI/CVBS)	
	Audio Interface	x1 2-pin UTP Video Output	
Interface	RS-485		
шепасе		- N1/A	
	Control Protocol	N/A	
	Up the Coax (Coaxitron) Support	Yes	
	OSD Buttons	Yes	
	Power Supply	DC12V±10%/AC24V±10%	
	Power Output	DC12V, Max. 100mA	
General	Power Consumption	Max. 6.5W	
	Operating Temperature	-30°C to +40°C	
	Operating Humidity	20-80% RH	
	Ingress Protection	IP66	
	Impact Resistance	IK10	
	Housing Materials	Aluminum Diecasting	
	RAL	RAL 9010 Pure White	
	Dimension	Ø110.8×81.8mm	
	Net Weight	≈450g	
	Gross Weight	≈650g	
Certification	n Certifications	CE	

RECOMMENDED ACCESSORIES


• RG59K-500


CP-BASE-1-V2 Concept Pro Small Junction Box
 CP-WM-1-V2 Concept Pro Small Wall Mount
 CP-PM-1-V2 Concept Pro Small In-ceiling/Tile Mount
 CP-TM-1-V2 Concept Pro Pole Mount
 CP-CM-V2 Concept Pro Corner Mount
 CP-RC-V2 Concept Pro Rain Cap
 RG59K-100 RG59 Coaxial Cable 100m (Black)


RG59 Coaxial Cable 500m (Black)

DIMENSIONS

All measurements are in mm.







ORDER CODE

• CVP5325IREL-AHD5M/2.8

Concept Pro 5MP 4-in-1 Analogue Fixed Compact External Dome

Concept Pro Lite 2MP AHD Wide

OTHER PRODUCTS IN THE RANGE

CVP5325IREL-AHD2M/WA

 CVP5325IREL-AHD2M/2.8 Concept Pro Lite 2MP AHD Fixed External Compact Vandal Dome Camera

Angle Fixed External Compact Vandal Dome Camera

 CVP5325IREL-AHD5M/WA Concept Pro Lite 5MP AHD Wide Angle Fixed External Compact Vandal Dome Camera

CVP5325IREL-AHD2M/2.8-SD Concept Pro Lite 2MP AHD Smoked Dome Fixed External Compact Vandal Dome Camera

Dome Camera (4mm)

CVP5325IREL-AHD5M/2.8-SD Concept Pro 5MP AHD Smoked

CVP5325IREL-AHD5M/2.8-SD Concept Fire SMF AFID Smoked

Dome Fixed External Compact Vandal

Dome Camera

CVP5325IREL-AHD2M/WA-SD Concept Pro Lite 2MP AHD Smoked Dome Wide Angle Fixed External Compact Vandal Dome Camera

CVP5325IREL-AHD5M/WA-SD Concept Pro 5MP AHD Smoked Dome Wide Angle Fixed External Compact Vandal Dome Camera

CVP5325IREL-AHD2M/2.8

Concept Pro 5MP 4-in-1 AHD Fixed Lens Compact Vandal Dome Camera



ACCESSORIES

CP-TM-1-V2

Concept Pro Small In-ceiling/Tile Mount



DIMENSIONS







Concept Pro Small Junction Box










CP-PM-1-V2

Concept Pro Small Pendant Mount





CP-WM-1-V2

Concept Pro Small Wall Mount













CP-PLM-V2

Concept Pro Pole Mount (can be combined with CP-BASE-2-V2)








CP-CM-V2

Concept Pro Corner Mount (can be combined with CP-BASE-2-V2)







CP-RC-V2