



# Concept Pro

**5MP**

**4mm  
Fixed  
Lens**


**30M  
IR**

**IP**

## CVP9316DEIREL-IP5M/4


### Concept Pro 5MP IP Enhanced Low Light Fixed External Turret Camera

The CVP9316DEIREL-IP5M/4 model is an IP camera that has been designed to deliver the highest image quality for demanding external environments. This weather-resistant external turret features a 4mm fixed lens, smart infrared LEDs with 30m illumination range, and provides crisp 5-megapixel video. It comes equipped with alarm and audio functionality for the most advanced installation needs. This camera is also designed for excellent compatibility with the Concept Pro range of network video recorders.




#### Deep Learning Motion Detection

Reduce false motion detection alarms by up to 95% using new Deep Learning Motion Detection technology. Trained with deep learning algorithms, the camera can recognise and trigger motion detection events only if a person is detected in the specified area. As a result, false alarms from sources such as lights, animals, foliage, weather, and other objects are effectively filtered and reduced.



#### Intelligent, Efficient Bit Rate Control

Reduce camera streaming bit rates by up to 90% by using Variable Bit Rate (VBR) or VBR+ smart bit rate control settings. These dynamic features maximise overall image quality while minimising camera stream bit rates. This results in lower network bandwidth usage and extended recording storage retention time.



#### Enhanced Low Light Performance

This model utilises an Enhanced Low Light CMOS sensor with greater light sensitivity, resulting in the camera capturing colour images long after standard CCTV cameras have switched to black & white night mode and brighter images in darker conditions.

### KEY FEATURES

- ◆ Max. 20FPS @ 5MP
- ◆ 4mm Fixed Lens
- ◆ Up to 30m Smart IR Illumination
- ◆ Deep Learning Motion Detection
- ◆ H.265 Video Codec & VBR+ Smart Bit Rate Control
- ◆ Alarm & Audio I/O
- ◆ Enhanced Low Light Performance

### OTHER FEATURES

- ◆ PoE/DC12V Power Input
- ◆ True WDR, ATW, BLC, Defog, 3D-DNR
- ◆ Auto/Manual Regions of Interest
- ◆ ONVIF Profile S Compliant
- ◆ IP66-rated

COMPATIBLE WITH



CONCEPT PRO  
IP RECORDING  
RANGE

# CVP9316DEIREL-IP5M/4

Concept Pro 5MP IP Enhanced Low Light Fixed External Turret Camera


# Concept Pro

## SPECIFICATION

Model/Feature	CVP9316DEIREL-IP5M/4	
Video Output Type	IP	
Image Sensor	1/2.8" Progressive Scan CMOS	
Signal System	PAL/NTSC	
Min. Illumination	Enhanced Low Light Performance - Colour: 0.004 Lux @ (F2.0, AGC ON) B&W: 0 lux with IR LEDs on	
Camera	Electronic Shutter	Auto/Manual, 1/25 to 1/5,000s
	S/N Ratio	≥48dB
	IR LEDs	x2
	IR Illumination Range	Max. 30m
	IR Control	Auto/Off
	Adaptable IR	Auto
	Pan/Tilt/Rotation Range	P: 0°-349°, T: 0°-80°, R: 0°-360°
Lens	Lens Type	Fixed Lens
	Mount Type	Built-in
	Focal Length	f=4mm
	Aperture	F1.6
	Angle of View	H: 78.4° / V: 59.8° / D: 97.2°
Video	Focus	Fixed Focus
	Iris	Fixed Iris
	Compression	H.265/H.264 with VBR+ Smart Codec Option
	Streaming Capability	Triple Streaming + SVC Stream
	Resolution	2592x1944, 2592x1520, 2304x1296, 2048x1536, 1920x1080, 1280x1024, 1024x768, 1280x720, 704x576, 704x480, 640x480, 640x360, 352x288, 352x240
	Frame Rate	Stream 1: Max. 20FPS @ 2592x1944, Max. 25FPS @ 2592x1520 Stream 2: Max. 25FPS @ 640x480 Stream 3: Max. 25FPS @ 640x480
	Bit Rate Control	CBR/VBR/VBR+
	Bit Rate	Stream 1: 1,000-8,000kbps Stream 2: 600-2,000kbps Stream 3: 600-2,000kbps
	Day/Night	True D&N with ICR (Auto/Day/Night/Schedule)
	Backlight Compensation	Yes
	Wide Dynamic Range	True WDR
	White Balance	ATW/Manual (Indoor/Fluorescent/Outdoor)
	Gain Control	Auto
	Noise Reduction	3D-DNR (Auto/Manual)
	Region of Interest	Auto/Manual (Max. 8 Regions)
	Defog	Yes
	Slow Shutter	Off/X2/X4/X8
	Image Setting	Mirror/Flip
Image Adjustment	Brightness, Contrast, Colour, Sharpness	
Privacy Masking	Yes (Max. 4 Areas)	
Motion Detection	Yes (Max. 4 Areas)	
Tamper Detection	Yes	
Basic Video Analytics	Yes (Line Crossing, Enter/Exit, Loitering, Stopping, Object Removed, Counter)	
Deep Learning Motion Detection	Yes (Human Detection)	
Deep Learning Video Analytics	-	
Transmission Distance	Max. 100m over Ethernet	
Network	Ethernet	x1 RJ45 10M/100M Ethernet
	Protocol	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, SMTP, FTP, UPnP, HTTP, HTTPS, SSL/TLS
	Interoperability	ONVIF Profile S, HTTP/RTSP API
	ONVIF Channels	Max. 4 Streams
	Streaming Method	Unicast/Multicast
Interface	Max. User Access	x10
	Edge Storage	Local PC (Snapshot/Recording)
General	Video Interface	-
	Alarm Interface	Alarm In x1, Alarm Out x1
	Audio Interface	Audio In x1 (RCA), Audio Out x1 (RCA)
	Audio Compression	G.711u-law (8kHz)
	RS-485	-
	Control Protocol	N/A
	Reset Button	Yes
	Power Supply	PoE 802.3af (Class 0)/DC12V
	Power Consumption	PoE: Max. 7.19W with IR on DC12V: Max. 4.7W with IR on
	Power Output	-
General	Operating Temperature	-20°C to +50°C
	Operating Humidity	0% to 90%
	Ingress Protection	IP66
	Vandal Resistance	-
	Housing Materials	Aluminum Diecasting
	RAL	CVP9316DEIREL-IP5M/2.8: RAL9010 Pure White CVP9316DEIREL-IP5M-G/2.8: RAL7021 Black Grey
	Dimensions	(Ø) 120mm x (H) 94.8mm
Certification	Net Weight	≈700g
	Gross Weight	≈850g
Certifications	CE/RoHS	

## DIMENSIONS

All measurements are in mm.



## ORDER CODE

- **CVP9316DEIREL-IP5M/4** Concept Pro 5MP IP Enhanced Low Light Fixed External Turret Camera (4mm)

## OTHER PRODUCTS IN THE RANGE

- **CVP9316DEIREL-IP5M/2.8** Concept Pro 5MP IP Enhanced Low Light Fixed External Turret Camera (2.8mm)
- **CVP9316DEIREL-IP5M G/2.8** Concept Pro 5MP IP Enhanced Low Light Fixed External Turret Camera (2.8mm) Grey
- **CVP9316DEIREL-IP5M-Z** Concept Pro 5MP IP Enhanced Low Light Motorised External Turret Camera
- **CVP9316DEIREL-IP8M/2.8** Concept Pro 8MP IP Enhanced Low Light Fixed External Turret Camera
- **CVP9316DEIREL-IP8M-G/2.8** Concept Pro 8MP IP Enhanced Low Light Fixed External Turret Camera - Grey

## RECOMMENDED ACCESSORIES

- **CP-BASE-1-V2** Concept Pro Small Junction Box
- **CP-WM-1-V2** Concept Pro Small Wall Mount
- **CP-PM-1-V2** Concept Pro Small Pendant Mount
- **CP-PLM-V2** Concept Pro Pole Mount
- **CP-CM-V2** Concept Pro Corner Mount
- **CAT6-305 305m** CAT6 Cable (Green)
- **VA-SW4/8/16POE-IP** 4/8/16 Channel PoE Switch

COMPATIBLE WITH



CONCEPT PRO IP RECORDING RANGE

# CVP9316DEIREL-IP5M/4

Concept Pro 5MP IP Enhanced Low Light Fixed External Turret Camera




## ACCESSORIES

## DIMENSIONS


### CP-BASE-1-V2

Concept Pro Small Junction Box





### CP-PM-1-V2

Concept Pro Small Pendant Mount




### CP-WM-1-V2

Concept Pro Small Wall Mount



### CP-PLM-V2

Concept Pro Pole Mount  
(can be combined with CP-BASE-1-V2)



### CP-CM-V2

Concept Pro Corner Mount  
(can be combined with CP-BASE-1-V2)

