



5MP

4mm Fixed Lens 30M IR

4 in 1

CVP9316IREL-AHD5M/4 CVP9316IREL-AHD5M-G/4

Concept Pro 5MP AHD Enhanced Low Light Fixed External Turret Camera (4mm)

The CVP9316IREL-AHD5M/4 model is a 4-in-1 analogue camera that has been designed to deliver the highest image quality for demanding external environments. This weather-resistant external turret features a 4mm fixed lens, smart infrared LEDs with 30m illumination range, and provides crisp 5-megapixel video with true wide dynamic range and enhanced low light performance. This camera is also designed for excellent compatibility with the Concept Pro range of hybrid digital video recorders.



True Wide Dynamic Range

With true wide dynamic range, this camera can capture sharp images throughout the entire field of view, even when there are severe differences between light levels.



Enhanced Low Light Performance

This CCTV camera utilises an Enhanced Low Light CMOS sensor with greater light sensitivity, resulting in the camera capturing colour images long after standard CCTV cameras have switched to black and white night mode.



Four-in-one solution

Don't be tied down to any single analogue platform. With Concept Pro 4-in-1 cameras you have the freedom to install whichever CCTV platform you like, whether you install AHD, TVI, CVI, or traditional analogue systems.

KEY FEATURES

Max. 20FPS @ 5MP

4mm Fixed Lens

Up to 30m Smart IR Illumination

4-in-1 Operation (AHD/TVI/CVI/CVBS)

Enhanced Low Light Performance

True Wide Dynamic Range

OTHER FEATURES

DC12V Power Input

Up the Coax Coaxitron Support

AGC, 3D-DNR, BLC

IP66-rated

ANALOGUE HD TYPICAL CABLE DISTANCE



DVR

	5MP	2MP	720P
COAX (RG59)	UP TO 500M	UP TO 500M	UP TO 500M
CAT5e	UP TO 200M	UP TO 305M	UP TO 350M
CAT6	UP TO 200M	UP TO 305M	UP TO 350M

*Approximate distances calculated using HD MasterBaluns.

Actual transmission range will vary depending on type and quality of cable and baluns.

CONCEPT PRO
AHD RECORDING
RANGE

CVP9316IREL-AHD5M/4 CVP9316IREL-AHD5M-G/4



Concept Pro 5MP AHD Enhanced Low Light Fixed External Turret Camera (4mm)


SPECIFICATION


Model/Fe	ature	CVP9316IREL-AHD5M/4 CVP9316IREL-AHD5M-G/4
	Image Sensor	1/2.8" Progressive Scan CMOS
	Video Output Type	AHD/TVI/CVI/CVBS
	Signal System	PAL/NTSC
	Min. Illumination	Colour: 0.4 lux (Enhanced Low Light)
		B&W: 0.04 lux (Enhanced Low Light)
		0 lux with IR on
Camera	Electronic Shutter	Auto
	S/N Ratio	≥50dB
	IR LEDs	x2
	IR Illumination Range	Max. 30m
	IR Control	On/Off
	Adaptable IR	Auto
	Pivot Axis	Pan: 0-349°, Tilt: 0-80°, Rotation: 0-360°
	Lens Type	Fixed
	Mount Type	Built-in Built-in
	Focal Length	f=4mm
Lens	Aperture	F2.0
	Angle of View	H:71°, V:58°,D:84°
	Focus	Fixed
	Iris	Fixed
	Resolution	5MP (2592x1944), 4MP (2560x1440), 2MP (1920 x 1080), SD (960 x 576)
	Frame Rate	AHD/TVI: 12.5/20FPS @ 5MP, 15/25/30FPS @ 4MP, 25/30FPS @ 2MP CVI: 25/30FPS @ 4MP, 25/30FPS @ 2MP
		CVI. 25/30FF3 @ 4WF, 25/30FF3 @ 2IVIF CVBS: 25/30FPS @ SD
	Day/Night	True Day & Night with ICR (Auto/Colour/B&W/EXT)
	Backlight Compensation	BLC/Global
	Wide Dynamic Range	True WDR
	White Balance	Pro/Gray World
Video	Gain Control	Auto
video	Noise Reduction	3D-DNR (Auto/Manual)
	Motion Detection	-
	Defog	
	Image Setting	Mirror
	Image Adjustment	Brightness, Sharpness, Contrast, Saturation
	Privacy Masking	Brightness, Gharphess, Contrast, Cataration
	Sens-Up	
	Transmission Distance	Max. 500m (1Vp-p 75Ω)
	Video Output	x1 1.0Vp-p 75Ω BNC (AHD/TVI/CVI/CVBS)
	Audio Interface	
	RS-485	
Interface	Control Protocol	N/A
	Up the Coax (Coaxitron) Support	Yes
	OSD Buttons	Yes
	Power Supply	DC12V±10%
	Power Output	-
General	Power Consumption	Max. 4.8W
	Operating Temperature	-30°C to +40°C
	Operating Humidity	20–80% RH
	Ingress Protection	IP66
	Impact Resistance	11-00
	Housing Materials	- Aluminum Diecasting
	RAI	CVP9316IREL-AHD5M/4: RAL 9010 Pure White
	NAL	CVP9316IREL-AHD5M/4: RAL 7011 Pure Writte CVP9316IREL-AHD5M-G/4: RAL 7021 Black Grey
	Dimension	Ø120 x (H) 94.8mm
	Net Weight	≈480g
	Gross Weight	≈630g
Certification	Certifications	CE

RECOMENDED ACCESSORIES

CP-BASE-1-V2	Concept Pro Small Junction Box
CP-WM-1-V2	Concept Pro Small Wall Mount
CP-PM-1-V2	Concept Pro Small Pendant Mount
CP-PLM-V2	Concept Pro Pole Mount
CP-CM-V2	Concept Pro Corner Mount
RG59K-100	RG59 Coaxial Cable 100m (Black)
RG59K-500	RG59 Coaxial Cable 500m (Black)

DIMENSIONS





ORDER CODES

CVP9316IREL-AHD5M/4

Concept Pro 5MP AHD Enhanced Low Light Fixed External Turret Camera (4mm)

CVP9316IREL-AHD5M-G/4

Concept Pro 5MP AHD Enhanced Low Light Fixed External Turret Camera (4mm) Grey

OTHER PRODUCTS IN RANGE

CVP9316IREL-AHD2M/4

Concept Pro Lite 2MP AHD Enhanced Low Light Fixed External Turret Camera (4mm)

+ CVP9316IREL-AHD2M-G/4

Concept Pro Lite 2MP AHD Enhanced Low Light Fixed External Turret Camera (4mm)

CVP9316IREL-AHD5M/2.8
 CVP9316IREL-AHD5M/2.8-G

Concept Pro Lite 5MP AHD Enhanced Low Light Fixed External Turret Camera

• CVP9316IREL-AHD2M/2.8

Concept Pro Lite 5MP AHD Enhanced Low Light Fixed External Turret Camera (grey) Concept Pro Lite 2MP AHD Enhanced Low

• CVP9316IREL-AHD2M-G/2.8

Concept Pro Lite 2MP AHD Enhanced Low Light Fixed External Turret Camera (Grey)

Light Fixed External Turret Camera

CVP9316IREL-AHD5M/4 CVP9316IREL-AHD5M-G/4



Concept Pro 5MP AHD Enhanced Low Light Fixed External Turret Camera (4mm)

ACCESSORIES DIMENSIONS

Concept Pro Small Junction Box










Concept Pro Small Pendant Mount





Concept Pro Small Wall Mount













Concept Pro Pole Mount (can be combined with CP-BASE-2-V2)







Concept Pro Corner Mount (can be combined with CP-BASE-2-V2)



